




Features

- Native WXGA (1280 x 800) Resolution
- 3,000 ANSI Lumens; 2,600:1 Contrast Ratio
- 0.37 Ultra Short Throw, Mic Input, 10 Watt Speakers x 2
- LAN Control/Display, USB Reader/Display
- Wireless Display (Optional)
- PointDraw™ Interactivity Ready (Optional)

Top View



Input and Output Terminals



- | | |
|--------------------------------|--------------------------------|
| 1 Audio-Out x1 | 6 HDMI x1 |
| 2 Audio-In & MIC-In, Audio L/R | 7 RS232 x1 |
| 3 S-Video/Video | 8 USB Type B & Mini B |
| 4 Monitor Out Output | 9 USB Type A x2 |
| 5 Computer I & 2 | 10 RJ45 x1 (Control & Display) |



Specifications

Projection System	DLP®																																
Native Resolution	WXGA (1280x800)																																
Brightness	3,000 ANSI lumens																																
Contrast Ratio	2,600:1 (Full on/Full off)																																
Display Color	1.07 Billion Colors																																
Lens	F=2.7, f=5.45mm																																
Aspect Ratio	Native 16:10 (5 aspect ratio selectable)																																
Throw Ratio	0.37 (87" @ 0.73m)																																
Image Size (Diagonal)	60~300"																																
Zoom Ratio	Fixed																																
Lamp Type	225W																																
Lamp (Normal/Eco Mode)	2,500/4,000 hrs (Normal/Economic mode)																																
Keystone Adjustment	ID, Vertical ±30 degrees																																
Projection Offset	125% ±5%																																
Resolution Support	VGA(640 x 480) to UXGA(1600 x 1200)																																
Horizontal Frequency	31K-102KHz																																
Vertical Scan Rate	23~120Hz																																
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p																																
Video Compatibility	NTSC, PAL, SECAM																																
3D Compatibility	PC: 120Hz Frame Sequential 3D for resolutions up to WXGA, PC: 60Hz Top-bottom 3D for resolutions up to SXGA+ Video: 60Hz Frame Sequential 3D for resolutions up to 480i																																
Interface	<table border="0"> <tbody> <tr> <td>Computer in (D-sub 15pin)</td><td>x 2 (Share with Component video in)</td></tr> <tr> <td>Monitor out (D-sub 15pin)</td><td>x 1</td></tr> <tr> <td>HDMI</td><td>x 1</td></tr> <tr> <td>Composite Video in (RCA)</td><td>x 1</td></tr> <tr> <td>S-Video in (Mini DIN 4pin)</td><td>x 1</td></tr> <tr> <td>Audio in (Mini Jack)</td><td>x 1</td></tr> <tr> <td>Audio L/R in (RCA)</td><td>x 1</td></tr> <tr> <td>Audio out (Mini Jack)</td><td>x 1</td></tr> <tr> <td>Microphone in (Mini jack)</td><td>x 1</td></tr> <tr> <td>Speaker</td><td>10W x 2</td></tr> <tr> <td>LAN (RJ45)</td><td>x 1</td></tr> <tr> <td>USB (TypeA)</td><td>x 2 (wireless display/USB reader/remote desktop)</td></tr> <tr> <td>USB (TypeB)</td><td>x 1 (work for PD pen/ FW download)</td></tr> <tr> <td>USB (Mini Type B)</td><td>x 1 (USB display)</td></tr> <tr> <td>RS232 (DB-9pin)</td><td>x 1</td></tr> <tr> <td>IR Receiver</td><td>x 2</td></tr> </tbody> </table>	Computer in (D-sub 15pin)	x 2 (Share with Component video in)	Monitor out (D-sub 15pin)	x 1	HDMI	x 1	Composite Video in (RCA)	x 1	S-Video in (Mini DIN 4pin)	x 1	Audio in (Mini Jack)	x 1	Audio L/R in (RCA)	x 1	Audio out (Mini Jack)	x 1	Microphone in (Mini jack)	x 1	Speaker	10W x 2	LAN (RJ45)	x 1	USB (TypeA)	x 2 (wireless display/USB reader/remote desktop)	USB (TypeB)	x 1 (work for PD pen/ FW download)	USB (Mini Type B)	x 1 (USB display)	RS232 (DB-9pin)	x 1	IR Receiver	x 2
Computer in (D-sub 15pin)	x 2 (Share with Component video in)																																
Monitor out (D-sub 15pin)	x 1																																
HDMI	x 1																																
Composite Video in (RCA)	x 1																																
S-Video in (Mini DIN 4pin)	x 1																																
Audio in (Mini Jack)	x 1																																
Audio L/R in (RCA)	x 1																																
Audio out (Mini Jack)	x 1																																
Microphone in (Mini jack)	x 1																																
Speaker	10W x 2																																
LAN (RJ45)	x 1																																
USB (TypeA)	x 2 (wireless display/USB reader/remote desktop)																																
USB (TypeB)	x 1 (work for PD pen/ FW download)																																
USB (Mini Type B)	x 1 (USB display)																																
RS232 (DB-9pin)	x 1																																
IR Receiver	x 2																																
Dimensions	330x154x278mm																																
Weight	4.1kg (9.1 lbs)																																
Power Supply	AC 100 to 240 V, 50/60 Hz																																
Power Consumption	310W, Standby<1W																																
Audible Noise	33/31 dBA (Normal/Economical Mode)																																
Display Languages	Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Hungarian/ Italian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (24 Languages)																																
Picture Mode	Dynamic/Presentation/sRGB/Cinema/User 1/User 2																																
Accessories (Standard)	Remote Control w/ Battery, Power Cord, User Manual CD/Quick Start Guide, Warranty Card, VGA(D-sub 15pin) Cable																																
Accessories (Optional)	<table border="0"> <tbody> <tr> <td>Wireless Dongle WDRL3070</td><td>P/N: 5J.J0614.A21</td></tr> <tr> <td>PD03 Pen Kit</td><td>P/N: 5J.J8E26.A01</td></tr> <tr> <td>PD03 Pen</td><td>P/N: 5J.J8E26.A11</td></tr> <tr> <td>Spare Lamp Kit</td><td>P/N: 5J.J2V05.001</td></tr> <tr> <td>Wall Mount</td><td>P/N: 5J.J4R10.011</td></tr> <tr> <td>3D Glass</td><td>P/N: 5J.J7L25.002</td></tr> <tr> <td>Carry Bag</td><td>P/N: 5J.J2V09.011</td></tr> <tr> <td>Remote</td><td>P/N: 5J.J2V06.001</td></tr> </tbody> </table>	Wireless Dongle WDRL3070	P/N: 5J.J0614.A21	PD03 Pen Kit	P/N: 5J.J8E26.A01	PD03 Pen	P/N: 5J.J8E26.A11	Spare Lamp Kit	P/N: 5J.J2V05.001	Wall Mount	P/N: 5J.J4R10.011	3D Glass	P/N: 5J.J7L25.002	Carry Bag	P/N: 5J.J2V09.011	Remote	P/N: 5J.J2V06.001																
Wireless Dongle WDRL3070	P/N: 5J.J0614.A21																																
PD03 Pen Kit	P/N: 5J.J8E26.A01																																
PD03 Pen	P/N: 5J.J8E26.A11																																
Spare Lamp Kit	P/N: 5J.J2V05.001																																
Wall Mount	P/N: 5J.J4R10.011																																
3D Glass	P/N: 5J.J7L25.002																																
Carry Bag	P/N: 5J.J2V09.011																																
Remote	P/N: 5J.J2V06.001																																
UPC / Part #	8400460-2824-4 / 9H.J5L77.34A																																
Limited Warranty	3-Years Parts/Labor / 1-Year or 2000 hours of lamp life																																

*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

MW870UST 10-15-14-BQca



BenQ Canada Corp.

Tel: (416) 363-2367 www.BenQ.ca


BenQ is a registered trademark of BenQ Corp. DLP® is a registered trademark of Texas Instruments. All rights reserved. Product names, logos, brands, and other trademarks featured or referred to in this material are the property of their respective trademark holders. Specifications subject to change without notice.



Because it matters

MW870UST Interactive Projector


Distance Chart



Screen Size				Distance from screen (mm)	Vertical offset (mm)
Diagonal		W (mm)	H (mm)		
Inch	mm				
40	1016	862	538	294	67
50	1270	1077	673	381	84
60	1524	1292	808	468	101
80	2032	1723	1077	642	135
100	2540	2154	1346	817	168
120	3048	2585	1615	991	202
150	3810	3231	2019	1253	252
200	5080	4308	2692	1689	337
250	6350	5385	3365	2125	421
300	7620	6462	4039	2561	505

Optional Interactivity Function

Required equipment list:



Dimensions

Units: mm

