

INTERACTIVE | TL650

FLAT PANEL



Highlights

Interactive displays have become one of the most powerful office tools today, replacing traditional meetings and trainings with a new style of business communication that's proven to enhance meeting efficiency, training effectiveness, collaborative discussion, and team building. A winning solution for your business, the BenQ Interactive Flat Panel T650 combines the power of optical touch panel and multimedia connectivity to maximize your presentations. Designed with safety and flexibility in mind, the T650 is easy and simple to install in any office setting using a VESA wall mount.



Optical Sensing Touch Technology

Built with the Optical Sensing Touch technology, the T650 allows you to control your computer directly by touching the screen. It's faster, easier and far more precise when all you need to do is point and touch with the tip of your finger. Connect your computer to the T650 with a USB cable to get started!



Optical Dual Touch Technology

Pair the T650 with Windows® 8 / Windows® 7 and watch the Optical Dual Touch Technology works its magic turning the displayed image or spreadsheet figure into a multi-touch screen. Trainer or speaker can invite two audiences to come up to the board for a quick contest and trial.



Ambient Light Sensor

The T650 is built with an ambient light sensor to detect the amount of ambient lighting in its surrounding and adjust the display setting accordingly without user intervention. This means the audience can always enjoy optimal picture quality in office.



Integrated Speaker

To help professional elites gain the competitive edge by enriching their meeting with multimedia resources, BenQ has built 12W speakers into the T650. The use of videos, music and sound effects make every presentation more engaging and effective.



Specifications	
LCD Size	65"
Light Source	Edge LED
Resolution	FHD 1920 x 1080 (pixels)
Aspect Ratio	16:09
Brightness (typ)	360 nits
Contrast Ratio (typ)	4000:1
Response Time (ms)	8ms
Frame Rate	60Hz
Viewing Angle (L/R: U/D)	178/178
Color gamut (x% NTSC)	72%
Panel Bit (8 or 10)	8 bit + FRC (1073.7M)
Weight without packing/with packing	71.5kg / 81.5kg
Dimension (WxHxD)	1515.8 x 888.6 x 114.15mm
Housing Material	Metal (NCT)
Wall Mounting	4 Holes (400 x 400mm)
Power	
Voltage	100 V ~ 240 V, 50/60Hz
Maximum (Watt)	310W
Standby (Watt)	<0.5W
Touch	
Technology	Dual Touch - Windows 7 & Windows 8. Single Touch - Windows XP, Windows Vista & MAC
Resolution (Points area function)	32767 x 32767
Capacity	2 simultaneous touches
Touch Output	USB 2.0
PC	Supports single touch for Windows XP, Windows Vista, Mac, Dual touch for Win8 / Win 7
Accuracy	+/- 6mm over 95% of touchable area
Audio	
Audio W (Amp)	12W x 2
IO	
Line in	Yes
Power (AC) Input / Output	Yes
Audio Output (L/R, RCA)	Yes
External Speaker Out (L/R)	Yes
Audio Input (L/R)	Yes (x2)
HDMI In	Yes
DVI Input \ Output	Yes
VGA In \ Out	Yes
USB (Touch to External PC)	Yes
RS232 Input \ Output	Yes
Component In (YPbPr, RCA)	Yes
S-Video In	Yes
Composite Video In \ Out (BNC)	Yes
Display Port Input	Yes
RJ45 Port	Yes
Features	
Sharpness Enhancement	Yes
Proof of Image Retention	Yes
DCR	13000:1
Picture in Picture (PIP)	Yes
De-Interlacing / Comb Filter	Yes
Color Processing	10 Bit
Build-In Video Wall Support	Yes
Scheduling	Yes
Ambient Light Sensor	Yes
Total Turn-on Time	Yes
Diagnostic DC Voltage	12v / 5v
Internal Temperature Sensor	Yes
Limited Warranty	3 Years on site Parts & Labor
UPC Code	8400460-2555-7

TL650 02-13-13-BQca

BenQ Canada Corp.

Tel: (416) 363-2367 | www.BenQ.ca

BenQ is a registered trademark of BenQ Corp. All rights reserved.

Product names, logos, brands, and other trademarks featured or referred to in the materials are the property of their respective trademark holders. Specifications subject to change without notice.



Enjoyment Matters