



Canada Monitor Quick Guide

BenQ Canada Main Website:

Contact your BenQ Regional Sales Manager or local dealer for more information.

Effective: September 2011

www.BenQ.ca

Model	Screen Size	Backlight	Native Resolution	Product Colour	Pixel Pitch	Brightness	Dynamic Contrast Ratio	Viewing Angle (R/L, U/D)	Response Time	Input Connectors	VESA™ Mounting	Stand	Features	EPEAT® Certification	Standard / Approvals
Consumer															
G925HD	18.5"	CCFL	1366 x 768	Black	0.3	200 cd/m ²	40,000:1	90° / 65°	5ms	DVI-D, D-Sub	100 mm x 100 mm	Tilt, Base Detachable	Senseye+Photo®	-	RoHS, ErP
G2222HDL	21.5"	LED	1920 x 1080	Black	0.248	250 cd/m ²	5M:1	170° / 160°	5ms	DVI-D, D-Sub	100 mm x 100 mm	Tilt, Base Detachable	Senseye 3®	Silver	ENERGY STAR® 5.0, ErP, RoHS
G2320HDB	23"	CCFL	1920 x 1080	Black	0.265	300 cd/m ²	40,000:1	170° / 160°	5ms	DVI-D, D-Sub	100 mm x 100 mm	Tilt, Base Detachable	Senseye+Photo®	-	RoHS
G2420HD	24"	CCFL	1920 x 1080	Black	0.276	300 cd/m ²	40,000:1	170° / 160°	2ms GTG	HDMI, DVI-D, D-Sub, Headphone Jack	100 mm x 100 mm	Tilt, Base Detachable	Senseye+Photo®	-	ENERGY STAR® 5.0, RoHS
G2450HM	24"	CCFL	1920 x 1080	Black	0.276	300 cd/m ²	50,000:1	170° / 160°	2ms GTG	HDMI, DVI-D, D-Sub, Headphone Jack	100 mm x 100 mm	Tilt, Base Detachable	Senseye 3®, Speakers	-	ENERGY STAR® 5.0, ErP, RoHS, TCO 5.0
G2750HM	27"	CCFL	1920 x 1080	Black	0.276	300 cd/m ²	50,000:1	170° / 160°	2ms GTG	HDMI, DVI-D, D-Sub, Headphone Jack	100 mm x 100 mm	Tilt, Base Detachable	Senseye 3®, Speakers	-	ENERGY STAR® 5.0, ErP, RoHS, TCO 5.0
Education / Government															
GL930	18.5"	LED	1366 x 768	Black	0.3	250 cd/m ²	12M:1	170° / 160°	5ms	DVI-D, D-Sub	-	Tilt, Base Detachable	Senseye 3®	-	Senseye 3®
GL2030	20"	LED	1600 x 900	Black	0.276	250 cd/m ²	12M:1	170° / 160°	5ms	DVI-D, D-Sub	-	Tilt, Base Detachable	Senseye 3®	Silver	ENERGY STAR® 5.0, ErP, RoHS



G925HD



G2222HDL



G2320HDB



G2420HD



G2450HM



G2750HM



GL930



GL2030



Canada Monitor Quick Guide

BenQ Canada Main Website:

Contact your BenQ Regional Sales Manager or local dealer for more information.

Effective: September 2011

www.BenQ.ca

Model	Screen Size	Backlight	Native Resolution	Product Colour	Pixel Pitch	Brightness	Dynamic Contrast Ratio	Viewing Angle (R/L, U/D)	Response Time	Input Connectors	VESA™ Mounting	Stand	Features	EPEAT® Certification	Standard / Approvals
Corporate / Government															
BL2201PU	22"	LED	1680 x 1050	Black	0.282	250 cd/m ²	12M:1	170° / 160°	5ms	DisplayPort™, DVI-D, D-Sub, Headphone Jack, Line-in, USB x 5	100 mm x 100 mm	Tilt, Base Detachable, Swivel, Pivot, Height-Adjustable	Senseye 3®, Speakers, Light / Proximity Sensors	Silver	ENERGY STAR® 5.0, ErP, RoHS, TCO 5.0
BL2400PU	24"	LED	1920 x 1080	Black	0.276	250 cd/m ²	20M:1	178° / 178°	8ms GTG	DisplayPort™, DVI-D, D-Sub, Headphone Jack, Line-in, USB x 5	100 mm x 100 mm	Tilt, Base Detachable, Swivel, Pivot, Height-Adjustable	Senseye 3®, A-MVA Panel, Speakers, Light / Proximity Sensors	Gold	ENERGY STAR® 5.0, ErP, RoHS, TCO 5.0
Premium / Consumer															
EW2420	24"	LED	1920 x 1080	Black	0.276	250 cd/m ²	20M:1	178° / 178°	8ms GTG	HDMI x 2, DVI-D, D-Sub, Headphone Jack, Line-in, USB x 5	100 mm x 100 mm	Tilt, Base Detachable	Senseye 3®, A-MVA Panel, Speakers	-	ENERGY STAR® 5.0, ErP, RoHS, TCO 5.0
VW2420H	24"	LED	1920 x 1080	Black	0.276	250 cd/m ²	20M:1	178° / 178°	8ms GTG	HDMI, DVI-D, D-Sub, Headphone Jack	-	Tilt, Base Detachable	Senseye 3®, A-MVA Panel	-	ENERGY STAR® 5.0, ErP, RoHS
EW2730	27"	LED	1920 x 1080	Black	0.311	300 cd/m ²	20M:1	178° / 178°	8ms GTG	HDMI x 2, DVI-D, D-Sub, Headphone Jack, Line-in, Line-out, USB x 5	100 mm x 100 mm	Tilt, Base Detachable	Senseye 3®, A-MVA Panel, Speakers, Remote Control	-	ENERGY STAR® 5.0, ErP, RoHS, TCO 5.0
Gaming															
XL2410T	23.6"	LED	1920 x 1080	Black	0.2715	300 cd/m ²	10M:1	170° / 160°	2ms GTG	HDMI, DVI-D-DL, D-Sub, Headphone Jack	100 mm x 100 mm	Tilt, Base Detachable, Swivel, Pivot, Height-Adjustable	Senseye 3®, NVIDIA® 3D Ready	-	ENERGY STAR® 5.0, ErP, RoHS, TCO 5.0
XL2420T	24"	LED	1920 x 1080	Black-Red	0.276	350 cd/m ²	12M:1	170° / 160°	2ms GTG	DisplayPort™ 1.2, HDMI 1.4 x 2, DVI-DL, D-Sub, USB x 4	100 mm x 100 mm	Tilt, Base Detachable, Swivel, Pivot, Height-Adjustable	Senseye 3®, NVIDIA® 3D Ready	-	ENERGY STAR® 5.0, ErP, RoHS, TCO 5.0



BL2201PU



BL2400PU




EW2420



VW2420H



EW2730



XL2410T



XL2420T