GL2055 Designed For Excellence



Features

- 20"Widescreen LED Monitor
- I 600 x 900 Native Resolution
- I2M:1 Ultra High Dynamic Contrast Ratio
- 5ms Superior Response Time
- Senseye[™] Technology
- Power Saving
- Windows 7 Compatible

GL2055 Images















UPC Code

Warranty Limited Warranty

| Specifications | |
|--|-------------------------------------|
| Product Color | Glossy Black |
| Back Light Unit | LED |
| LCD Size | 20"W |
| Aspect Ratio | 16:9 |
| Resolution (Native) | 1600 x 900 |
| Display Area | 442.8 x 249.1 |
| Pixel Pitch (mm) | 0.276 |
| Brightness (typ.) | 200 cd/m² |
| Contrast (typ.) | 700:1 |
| DCR (Dynamic Contrast Ratio) (typ.) | 12M:1 |
| Panel Type | TN |
| Viewing Angle (L/R;U/D) (CR>=10) | 90/65 |
| Response Time (Tr+Tf) typ. | 5ms |
| Display Colors | 16.7 million |
| Color Gamut | 72% |
| Hor. Frequency (KHz) | 30~83 |
| Ver. Frequency (Hz) | 50~76 |
| Video Bandwidth (MHZ) | 165 MHz |
| Input Connector | D-sub / DVI |
| Power Supply (90~264 AC) | Built-in |
| Power Consumption (Base on Energy star) | 16W |
| Power Consumption (On mode) | 23W |
| Power saving mode | <0.3W |
| K Locker | Yes |
| Dimensions with Stand (HxWxD) | 371 x 491 x 164 mm |
| Dimensions w/o Stand(HxWxD) | 300 x 491 x 57 mm |
| Weight (Net/Gross) | 3.0 / 4.2 kg |
| Special Features | |
| Senseye | Senseye 3 |
| Vista | Premium |
| Win7 | Yes |
| HDCP | Yes |
| Color Temperature | Reddish / Normal/ Bluish /user mode |
| OSD Language | 17 languages |
| VESA Wall Mounting | 100x100mm |
| Tilt (down/up) | -5/15 |
| Dynamic Power Saving (DPS) | Yes |
| Included Accessories | VGA |
| | 1 |

8400460-2691-2

3 Years Parts & Labor

GL2055 07-02-12-BQca







