GP2 Battery

- Up to 3 hours battery life per charge*
- Detachable & Rechargable
- 5600mAh



Part Number/UPC code	5J.J3C01.001/8400460-2085-9
_	1.1.1.

Type Lithium-ion Technology **Electrical Rating** 14.8V 5600mAh 82.88Wh **Dimensions** $134.4 \times 47.8 \times 124.1 \text{ mm}$

Weight 485g

300 cycles charging Battery cycle life

Charging time 3.5 hours for full battery charge

3 hrs battery life @ 100 Ansi Lumens (1hr @ 200 Ansi Lumens) Battery life*

(The battery life differs depending on daily use.)

LED color: LED Indicator: Status: Condition: Power on / Standby mode Blue blinking Charging Battery + Adaptor Blue solid on **Fully Charged** Power on / Standby mode

LED Indicator: Status: Condition: LED color: Battery capacity (100%~10%) Power on / Standby mode LED off Battery only Power on / Standby mode Battery capacity (<10%) Red blinking


(System warning message occurs with low power battery. At 10% power, system will automatically shut down)


Operating Specification Recommendations

- I. Keep the battery connected to the projector even when the projector is connected to a wall outlet.
- 2. While connected to battery, LED Mode in Settings will be set to Eco, you can play a video from any source for about three hours at 100AL when the battery is fully charged. (If LED Mode in Settings is changed to Normal, the battery life will be shortened to about one hour at 200AL.)
- 3. Use the battery under normal conditions, temperature (25±3)° C, absolute humidity: 65±20%
- 4. Discharging temperature range is $0\sim60^{\circ}$ C, beyond which it will result in decadence of the battery performance and shortness of its life.


Operation Instructions

Installing Battery to GP2









SpecSheetGP2Battery 042512BQca





