

IL460 | Interactive Flat Panel

Highlights

Interactive displays have become one of the most powerful office tools today, replacing traditional meetings and trainings with a new style of business communication that's proven to enhance meeting efficiency, training effectiveness, collaborative discussion, and team building. A winning solution for your business, the BenQ Interactive Flat Panel IL460 combines the power of infrared touch panel and multimedia connectivity to maximize your presentations. Designed with safety and flexibility in mind, the IL460 is easy and simple to install in any office setting using a VESA wall mount.



Infrared 6 Points Touch Technology

Pair the IL460 with Windows® 8 / Windows® 7 and watch the infrared touch technology work its magic turning the displayed image or spreadsheet figure into a multi-touch screen. Trainer or speaker can invite audiences to come up to the board for a quick contest and trial.





Ambient Light Sensor

The IL460 is built with an ambient light sensor to detect the amount of ambient lighting in its surrounding and adjust the display setting accordingly without user intervention. This means the audience can always enjoy optimal picture quality in office and classroom.



Integrated Speaker

To help professional elites gain the competitive edge by enriching their meeting with multimedia resources, BenQ has built 12W speakers into the IL460. The use of videos, music and sound effects make every presentation more engaging and effective.



- 1 AC OUT
- 2 AC IN
- 3 AC SWITCH ON/OFF
- 4 USB
- 5 SPEAKERS (R/L)
(IL650 not available)
- 6 AUDIO OUT (R/L)

- 7 AUDIO IN (AUDIO2)
- 8 AUDIO IN (AUDIO1)
- 9 VGA IN
- 10 VGA OUT
- 11 AV IN
- 12 AV OUT
- 13 VIDEO IN (S-VIDEO)
- 14 VIDEO IN (YPbPr)
- 15 RS232C IN / OUT
- 16 DVI-IN
- 17 HDMI
- 18 DISPLAY PORT
- 19 RJ-45



Specifications

Panel	LCD Size	46"
	Light Source	Edge LED
	Active Area (mm)	1018.08(H) x 572.67(V)
	Resolution	FHD 1920 x 1080 (pixels)
	Aspect Ratio	16:9
	Brightness	500 nits (typ.)
	Contrast Ratio	4000:1 (typ.)
	Response Time (ms)	6.5ms (typ.)
	Pixel Pitch	0.53025 (H) x 0.53025 (V) mm
	Frame Rate	60 Hz
	Viewing Angle	178 degree (H) / 178 degree (V)
	Light Life	50,000 hrs (typ.)
	Color gamut (x% NTSC)	72%
	Panel Bit	10 bit (8bit+FRC), 1073.7M
Power	Voltage	100 V ~ 240 V, 50 Hz / 60 Hz
	Maximum (Watt)	<150W
	Typical (Watt)	132W
	Standby (Watt)	<0.5W (only VGA wake-up)
Touch	Power Off (Watt)	<0.5W
	Touch points	6 points simultaneously
	OS supported	WinXP, Win7, Win8, Mac 10.4~10.10, Linux: Fedora 15 & Ubuntu 12.10
	Touch Driver Free	separated driver needed for Mac and Linux
Glass Environment	Tempered glass	8H
	Operation Temp (dC)	0°C ~ 40°C
	Storage Temp (dC)	-20°C ~ 60°C
	Storage Humidity	10% ~ 90% RH
Audio	Operating Humidity	10% ~ 80% RH
	Display Orientation	Landscape / Portrait
	Usage (hrs/days)	24 hours / 7 days
	Audio Input (L/R, RCA)	x1
AC Power	Audio Output (L/R, RCA)	x1
	Internal Spk	12W x 2
	Line in (3.5mm)	x1
	Power (AC) Input	x1
I/O	Power (AC) Output	x1
	Power switch	x1
	VGA In	x1
	VGA Output	x1 (3x3 Daisy Chain)
Control	DVI-D Input	x1
	HDMI Input	x1
	Composite video In (BNC)	x1
	Composite video Out (BNC)	x1
ME	Component In (RCA)	x1
	S-Video In	x1
	Display Port Input	x1
	RS232 Input	x1
Language Accessory	RS232 Output	x1
	RJ45 Port	x1
	FW Update	RS232/LAN
	Weight (without / with packing)	27.7/32.5 kg
Number	Dimension (WxHxD)	1066x621x100 mm
	Bezel Width (T/B/L/R)	22.5/22.5/22/22 mm
	Wall Mounting	400x200 (4 holes)
	OSD	EN/EF/SP/EP/CN/TC
Software Compatible	Remote Controller	x1
	PWR Cord	1.8 meter
	VGA Cable	x1
	Quick start guide	x1
Warranty	USB Cable (1.8M) for Touch (A-B)	x1
	Touch Pen (Stylus)	Yes (2pcs)
	UPC code	8400460-2883-1
	BenQ Part Number	9H.F09PM.NA4
Features	Multiple display administrator	Yes
	Warranty	3-Year
	Image Setting, VGA Daisy Chain, RS232 Control Daisy Chain, ID Setting, Sharpness Enhancement, Proof of Image Retention, Dimming Control (Adaptive Contrast), Picture in Picture (PIP), Picture by Picture (PBP), HDMI-HDCP, Scheduling, Ambient Light Sensor, Internal Temperature Sensor, CEC Control	

BenQ Canada Corp.

Tel: (416) 363-2367 www.BenQ.ca

BenQ is a registered trademark of BenQ Corp. All rights reserved. Product names, logos, brands, and other trademarks featured or referred to in the material are the property of their respective trademark holders. Specifications subject to change without notice.
IL460 02-03-15-BQca

BenQ

Because it matters