


BenQ Digital Projector

MP772 ST



HIGHLIGHTS

- Short Throw (0.6 Throw Ratio)
- Filter Free Design
- No Color Decay
- Crestron LAN Control
- 2500 ANSI Lumens
- XGA Native Resolution
- BrilliantColor™
- 3D Color Management
- VIDI™
- 6 Segments Color Wheel
- Keystone ± 30 Degree
- 5W x 2 Speakers
- Variable Audio Out
- Closed Captioning



Projection System	DLP® technology by Texas Instruments®	
Native Resolution	XGA (1024 x 768)	
Brightness	2500 ANSI lumens	
Contrast Ratio	2400:1 (Full on/Full off)	
Keystone	Manual Vertical ± 30 Degree	
Aspect Ratio	4:3 Native, 16:9 Selectable	
Color	Full 16.7 million color palette	
Lens	F=2.6, f=6.9 mm	
Zoom Ratio	Fixed	
Image Size (Diagonal)	61" to 300"	
Throw Ratio	0.61:1 (81"@1M)	
Lamp	210W, 3000/4000 hours (Normal/Economic mode)	
Computer Compatibility	VGA(640 x 480) to SXGA(1280 x 1024)	
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i	
Video Compatibility	NTSC, PAL, SECAM	
Horizontal Frequency	31-93 kHz	
Vertical Scan Rate	48-86 Hz	
Input Terminals	PC	Analog RGB: D-sub 15 pin x 2(shared with Component) S-Video: Mini Din 4 pin x 1 Composite Video: RCA x 1
	Audio	Audio L/R : RCA x 2 Stereo Mini Jack x 1
Output Terminals	PC	D-sub 15 pin x 1 Variable Audio Out : Stereo Mini Jack x 1
	Audio	5W x 2
Control Terminal	Serial Connector : RS232 9 pin x 1 RJ45 x 1	
Dimensions(W x H x D)	11.4 x 3.7 x 10.9 inch (290 x 94 x 278.6 mm) with Lens	
Weight	7.7 lbs (3.5kg)	
Power Supply	100 to 240 VAC, 50/60 Hz	
Power Consumption	295W, Standby < 1W	
Audible Noise	32/27 dB (Normal/Economic mode)	
On-Screen Display Languages	Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Hungarian/ Italian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (24 Languages)	
Picture Modes	Dynamic Mode	Presentation Mode
	sRGB Mode	Cinema Mode
	User 1 Mode	User 2 Mode
Functions	BrilliantColor™	Blank
	VIDI™	Panel Key Lock
	3D Color Management	Auto Off
	Crestron LAN Control	Security Password
	Closed Captioning	HDTV Compatible
	Digital Zoom (x2)	High Altitude Mode
	Variable Audio Out	"Q?" Hot Key for FAQ
	Quick Cooling	3D Ready
	Quick Auto Search	Freeze
	Quick Start Guide	VGA Cable
Accessories (Standard)	Manual CD	Power Cord
	Remote Control w/battery	
Accessories (Optional)	Presentation Plus	Spare Lamp Kit
	RS232 Cable	Soft Carry Case