

DIGITAL
PROJECTOR

MS500



Features


- Native SVGA Resolution (800x600)
- 2500 ANSI Lumens; 4000:1 Contrast Ratio
- Long Lamp Life, Virtually Color Decay Free
- 3D Ready; Closed Captioning; Digital Zoom 2x
- Quick Cooling; Variable Audio Out



Specifications

Projection System	DLP
Native Resolution	SVGA(800 x 600)
Brightness	2500 ANSI Lumens
Contrast Ratio	4000:1
Display Color	1.07 Billion Colors
Lens	F=2.56-2.8, f=21-23.1mm
Aspect Ratio	Native 4:3 (5 aspect ratio selectable)
Throw Ratio	1.86 ~2.04 (52.5"@ 2m)
Image Size Diagonal	24" ~ 300"
Zoom Ratio	1.1:1
Lamp Type	220W
Lamp Life (Normal/Eco Mode)	4500/6000 hours
Keystone Adjustment	1D, Vertical +/- 40 degrees
Projection Offset	110%±5%
Resolution Support	VGA (640x480) to UXGA (1600x1200)
Horizontal Frequency	31-99 kHz
Vertical Scan Rate	28-120 Hz
Compatibility	HDTV Compatibility: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p Video Compatibility: NTSC, PAL, SECAM 3D Compatibility: PC: 120Hz Frame Sequential 3D for resolutions up to WXGA.
Interface	Computer In (D-Sub 15pin) x2 (shared with Component) Monitor Out (D-Sub 15 pin) x1 Composite Video In (RCA) x1 S-Video In (Mini DIN 4pin) x1 Audio In (Mini Jack) x1 Audio Out (Mini Jack) x1 Speaker 2W x1 USB (Type Mini-B) x1 (Download & Page Up /Down) RS232 (DB-9Pin) x1
Dimensions (WxHxD)	11.3" x 3.95" x 9.157"
Weight	5.5 lbs (2.5 kgs)
Power Supply	AC 100 to 240 V, 50/60 Hz
Power Consumption	270W (Typical), Standby <1W
Audible Noise	33/27 dBA (Normal/Economic mode)
On-Screen Display Languages	English/ France/ Germany/ Italian/ Spanish/ Russian/ Traditional Chinese/ Simplified Chinese/ Japanese/ Korean/ Swedish/ Dutch/ Turkish/ Czech/ Portuguese/ Thai/ Polish/ Hungarian/ Croatian/ Romanian/ Norwegian/ Danish/ Bulgaria/ Finnish/ Indonesian/ Greek/ Hindi/ Arabic (28 Languages)
Picture Mode	Dynamic/Presentation/sRGB/Cinema/User 1/User 2
Accessories (Standard)	Remote Control w/ Battery, Power Cord, User Manual CD, Quick Start Guide, Warranty Card, VGA (D-sub 15 pin) Cable
Accessories (Optional)	Presentation Plus P/N:65.J9306.002 Spare Lamp Kit P/N:5J.J5205.001 3D Glasses P/N:5J.J0T14.011 Universal Ceiling Mount P/N:5J.J2K01.001 Carrying Bag P/N:5J.J3T09.001

Input and Output Terminals



- | | |
|-----------------------------|----------------------------|
| 1 USB (Mini-B) | 6 S-Video (Mini DIN 4-pin) |
| 2 Monitor Out (D-sub 15pin) | 7 Video Out (RCA Jack) |
| 3 Computer-1 (D-sub 15pin) | 8 Audio In (Mini Jack) |
| 4 Computer-2 (D-sub 15pin) | 9 Audio Out (Mini Jack) |
| 5 RS232 (DB-9pin) | |

*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

MS500 6-6-11-US



BenQ Canada Corp.

Tel: (416) 363-2367 www.BenQ.ca

BenQ is a registered trademark of BenQ Corp. DLP is a registered trademark of Texas Instruments. All rights reserved. Corporate and trademarks are the property of their respective companies. Specifications subject to change without notice.



Enjoyment Matters