




*lens is not included

Features

- WUXGA (1920X1200) Resolution
- 7,000 ANSI Lumens
- 2,800:1 Contrast Ratio
- Dual Lamp System
- HDBaseT Connectivity
- Flexible Placement Options for Multiple Applications
- Interchangeable Lenses and Color Wheels
- Powered Zoom, Focus, and Lens Shift

Input and Output Terminals



- | | |
|-------------------------------|------------------------------------|
| 1 HDBaseT/ LAN | 7 DisplayPort |
| 2 Computer 1 in (D-sub 15pin) | 8 RS232 (DB-9pin) |
| 3 3D Sync Out | 9 12V Trigger |
| 4 Monitor out (D-sub 15pin) | 10 USB (Type B) |
| 5 DVI-D in | 11 Wired Remote |
| 6 HDMI | 12 Computer 2 in (5BNC, R/G/B/H/V) |

Specifications

Projection System	DLP®
Native Resolution	WUXGA (1920X1200)
Brightness	7,000 ANSI lumens
Contrast Ratio	2,800:1 (Dual Lamp and Standard Lens)
Display Color	1.07 Billion Colors
Aspect Ratio	Native 16:10 (5 aspect ratio selectable)
Image Size Diagonal	80~500"
Lamp Type	350W x 2
Lamp Life	2,000/2,500 hours
Keystone Adjustment	1D, Vertical ± 30 degrees
Resolution Support	NTSC, PAL, SECAM
Horizontal Frequency	15K~91kHz
Vertical Scan Rate	48Hz~120Hz
Compatibility	HDTV Compatibility: 480i, 480p, 576i, 567p, 720p, 1080i, 1080p
Interface	Computer 1 in (D-sub 15pin) x 1 Computer 2 in (5BNC, R/G/B/H/V) x 1 Monitor out (D-sub 15pin) x 1 HDMI (1.4a) x 1 (Compatible with HDCP) DVI-D in x 1 (Compatible with HDCP) LAN (RJ45) x 1 (LAN Control) USB (Type B) x 1 (Download) HDBaseT x 1 (Share with RJ45) DisplayPort x 1 12V Trigger x 1 RS232 (DB-9pin) x 1 Wired Remote x 1 IR Receiver x 2 (Front+Rear)
Dimensions (WxHxD)	20" x 9" x 21" / 510 x 230 x 540 mm
Weight	46.2 lbs / 21 kgs (Without lens)
Power Supply	AC 100 to 240 V, 50/60 Hz
Stand-by Power Consumption	<0.5W (Only Power button on remote and keypad can work)
Acoustic Noise (Typ./Eco.)	41/36 db
Operating Temperature	5~40° C
Accessories (Standard)	Remote Control w/ Battery, Power Cord, User Manual CD, Quick Start Guide, Warranty Card, VGA(D-sub 15pin) Cable, Lens cover, 2 Color Wheels
Accessories (Optional)	Spare Lamp Kit P/N: 5J.JC705.001 Ceiling Mount P/N: 5J.JCY10.001 Remote Control P/N: 5J.JC706.001 Optional Lens: (see reference chart)
UPC Code / P/N	8400460-3107-7 / 9H.JCY77.26E
Limited Warranty	3 years warranty, 1 year/2000 hours lamp life

*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

BenQ Lens	P/N	Zoom Ratio	Throw Ratio	Lens Shift (Powered)	Marketing Model
STD Lens	5JJAM37.001	1.3:1	1.73~2.27	0-50% Vertical; +-10% Horizontal	PZL-001
Wide Fix	5JJAM37.011	Fixed	0.76	NA	PFL-011
Wide Zoom	5JJAM37.021	1.41:1	1.25~1.79	0-50% Vertical; +-10% Horizontal	PZL-021
Long Zoom 1	5JJAM37.031	1.5:1	3.58~5.38	0-50% Vertical; +-10% Horizontal	PZL-031
Long Zoom 2	5JJAM37.041	1.55:1	5.31~8.26	0-50% Vertical; +-10% Horizontal	PZL-041
Semi Long Zoom	5JJAM37.051	1.65:1	2.22~3.67	0-50% Vertical; +-10% Horizontal	PZL-051
Ultra Wide Zoom	5JJAM37.061	1.25:1	0.75~0.93	0-45% Vertical; +-10% Horizontal	PZL-061

Lens Images



BenQ.us • BenQ.ca

BenQ is a registered trademark of BenQ Corp. All rights reserved. Product names, logos, brands, and other trademarks featured or referred to in this material are the property of their respective trademark holders. Specifications subject to change without notice.

PU9730 | 12415_BQus


Because it matters

PU9730 Digital Projector

Distance Chart and Screen Size

Screen Size						5JJAM37.011		5JJAM37.021				5JJAM37.001				5JJAM37.051			
Diagonal						Wide Fix Lens		Wide Zoom Lens				STD Lens				Semi long Zoom1			
Width						N/A		Wide		Tele		Wide		Tele		Wide		Tele	
Height(B)						N/A		Wide		Tele		Wide		Tele		Wide		Tele	
(inch)	(m)	(inch)	(m)	(inch)	(m)	(inch)	(m)	(inch)	(m)	(inch)	(m)	(inch)	(m)	(inch)	(m)	(inch)	(m)	(inch)	(m)
40	1.02	34	0.86	21	0.54	25.1	0.64	41.4	1.05	59.9	1.52	57.2	1.45	75.8	1.93	73.6	1.87	124.1	3.15
50	1.27	42	1.08	26	0.67	31.8	0.81	52.3	1.33	75.4	1.92	72.1	1.83	95.5	2.42	92.9	2.36	155.9	3.96
60	1.52	51	1.29	32	0.81	38.5	0.98	63.1	1.60	90.9	2.31	87.1	2.21	115.1	2.92	112.1	2.85	187.8	4.77
80	2.03	68	1.72	42	1.08	52.0	1.32	84.9	2.16	121.8	3.09	117.0	2.97	154.3	3.92	150.5	3.82	251.4	6.39
100	2.54	85	2.15	53	1.35	65.5	1.66	106.6	2.71	152.7	3.88	147.0	3.73	193.5	4.92	188.9	4.80	315.0	8.00
120	3.05	102	2.58	64	1.62	78.9	2.01	128.4	3.26	183.6	4.66	176.9	4.49	232.8	5.91	227.6	5.78	378.6	9.62
150	3.81	127	3.23	79	2.02	99.1	2.52	161.0	4.09	230.0	5.84	221.8	5.63	291.6	7.41	285.0	7.24	474.1	12.04
180	4.57	153	3.88	95	2.42	119.3	3.03	193.6	4.92	276.4	7.02	266.7	6.77	350.5	8.90	342.6	8.70	569.5	14.47
200	5.08	170	4.31	106	2.69	132.8	3.37	215.3	5.47	307.3	7.81	296.6	7.53	389.7	9.90	381.0	9.68	633.1	16.08
300	7.62	254	6.46	159	4.04	200.1	5.08	324.0	8.23	461.9	11.73	446.3	11.34	585.9	14.9	573.2	14.56	951.2	24.16
400	10.16	339	8.62	212	5.38	267.4	6.79	432.7	10.99	616.6	15.66	595.9	15.14	782.3	19.87	765.3	19.44	1269.7	32.25
500	12.70	424	10.77	265	6.73	334.8	8.50	541.5	13.75	771.2	19.59	745.6	18.94	978.3	24.85	957.4	24.32	1587.8	40.33



Screen Size						5JJAM37.031				5JJAM37.041				5JJAM37.061			
Diagonal						Long Zoom 1 Lens				Long zoom 2 Lens				Ultra Wide zoom Lens			
Width						Wide		Tele		Wide		Tele		Wide		Tele	
Height(B)						Wide		Tele		Wide		Tele		Wide		Tele	
(inch)	(m)	(inch)	(m)	(inch)	(m)	(inch)	(m)	(inch)	(m)	(inch)	(m)	(inch)	(m)	(inch)	(m)	(inch)	(m)
40	1.02	34	0.86	21	0.54	118.7	3.01	181.0	4.60	173.9	4.42	277.7	7.05	24.5	0.62	31.1	0.79
50	1.27	42	1.08	26	0.67	149.7	3.80	227.6	5.78	220.2	5.59	350.0	8.89	31.1	0.79	39.2	1.00
60	1.52	51	1.29	32	0.81	180.7	4.59	274.1	6.96	266.6	6.77	422.3	10.73	37.6	0.96	47.4	1.20
80	2.03	68	1.72	42	1.08	242.7	6.16	367.3	9.33	359.4	9.13	567.0	14.40	50.8	1.29	63.8	1.62
100	2.54	85	2.15	53	1.35	304.3	7.73	460.4	11.70	452.1	11.48	711.6	18.07	63.9	1.62	80.2	2.04
120	3.05	102	2.58	64	1.62	366.7	9.31	553.6	14.06	544.9	13.84	856.2	21.75	77.1	1.96	96.6	2.45
150	3.81	127	3.23	79	2.02	459.4	11.67	693.3	17.61	684.0	17.37	1073.1	27.26	96.8	2.46	121.1	3.08
180	4.57	153	3.88	95	2.42	552.4	14.03	833.0	21.16	823.1	20.91	1290.1	32.77	116.5	2.96	145.7	3.70
200	5.08	170	4.31	106	2.69	614.7	15.6	926.4	23.53	915.9	23.26	1434.7	36.44	129.7	3.29	162.1	4.12
300	7.62	254	6.46	159	4.04	924.0	23.47	1392.1	35.36	1379.6	35.04	2157.8	54.81	195.4	4.96	244.0	6.20
400	10.16	339	8.62	212	5.38	1233.9	31.34	1857.9	47.19	1843.3	46.82	2880.9	73.18	261.2	6.63	325.9	8.28
500	12.70	424	10.77	265	6.73	1543.7	39.21	2323.6	59.02	2307.1	58.60	3604.0	91.54	326.9	8.30	407.7	10.36



Ceiling Mount Chart

Dimensions

Units: inch / mm



Because it matters