RP55 | + | Interactive Flat Panel

Highlights

Adopting an open system coupled with interactivity, BenQ delivers a future proof system with the RP-series. The RP-series largescreen display utilizes LED backlighting to deliver environmental and functional benefits. Featuring a full-HD model built with two 12W speakers, and up to 6-points of touch recognition, the RPseries enhances the interactive experience.

6-Points Touch Technology

An advanced touch screen not only provides a responsive, highprecision interface even for writing, but it enables multiple people to interact and collaborate simultaneously. By making the most use of the expansive screen area, increasing participation, and stimulating enthusiasm, RP55 I+ genuinely realize the full potential of IFP technology


Ambient Light Sensor

Automatic brightness adjustment not only ensures the best viewing experience regardless of light levels in the room, but also protects the eyes and ensures excessive brightness is not wasted when unnecessary, reducing power consumption by up to 50%.

Front I/O and Pen Tray

USB and HDMI ports, as well as a microphone jack, are located on the front panel, making it easy for teachers or speakers to plug in peripheral devices. A pen tray provides a handy place keep an IFP stylus and other tools to enhance a presentation, providing fast access and avoiding needless interruption.







Specifications		
Panel	LCD Size	55"
	Light Source	Edge LED
	Active Area (mm)	1244.6(H) x 720.9(V)
	Resolution	FHD 1920 x 1080 (pixels)
	Aspect Ratio	16:9 350 nits
	Brightness Contrast Ratio	1400:1
	Response Time (ms)	8ms
	Pixel Pitch	0.630 mm
	Frame Rate	60Hz
	Viewing Angle	178 degree (H) / 178 degree (V)
	Light Life	50,000 hrs (typ.)
	Color gamut (x% NTSC)	68%
Power	Panel Bit Voltage	8bit 100V~240V, 50-60Hz
	-	
	Maximun (Watt)	170W
	Typical (Watt)	140W
	Standby (Watt)	< 0.5W (only VGA wakeup)
	Power Off (Watt)	< 0.5W
Touch	Wake Up	All
TOUCH	Touch points	6 points simutaneously Win 7, Win 8, Chrome OS 34.0.1847.134, MAC
	OS supported	10.6~10.10, Linux
	Touch Driver Free	Yes; separated driver for Mac 10.10
Glass	Tempered glass	5mm (Anti glare 80%)
Environment	Operation Temp (dC)	0-40 degC
	Storage Temp (dC)	-20-60degC
	Storage Humidity	10%-90%RH non-condensing
	Operating Humidity Display Orientation	10%-80%RH non-condensing Landscape
	Usage (hrs/days)	18 hours/days
Audio	Audio Input (L/R, RCA)	x1
, tag. 5	Audio Output (L/R, RCA)	x1
	Internal Spk	12W x 2
	Line in (3.5mm)	x1
AC Power	Power (AC) Input	x1
	Power (AC) Output	x1
I/O	Power switch VGA In	x1 x1
	VGA III VGA Output	x1
	HDMI Input	x2
	Composite video In (BNC)	x1
	Composite video Out (BNC)	x1
	Component In (YPbPr, RCA)	x1
	S-Video In	x1
	Display Port Input	x1
	USB port (for USB playback) RJ45 Port	x1 x1
Control	RS232 Input	x1
	RS232 Output	x1
	·	
	RJ45 Port	x1
	FW Update	RS232/LAN
ME	Weight (without / with packing)	45/53 kg
	Dimension (WxHxD)	1271.4x833x210mm (with pentray, IO BOX)
	` '	1271.4x742x111.6mm (Without Pentray. IO Box)
	Bezel Width (T/B/L/R)	29.8/29.8/29.8mm
	Wall Mounting	VESA standard; 400x400 (4 holes)
	VESA Hole (for Media Player)	VESA standard: 100x100; 75x75 (7 holes)
	Pen Tray	x1
	Handle	x2
Language	OSD	EN/EF/SP/EP/CN/TC/GM/DT/PL/RS/CZ/DN/SW/IT/RM/FN
	OSD	NG/GK/TK/AB/JP (21L)
Accessory	Remote Controller	x1
	PWR Cord	1.8 M
	VGA Cable	x1
	Quick start guide	x1
	USB Cable (Touch)	x1 (1.8M)
	Touch Pen (Stylus)	x2
Software Compatible	EZ-Suite (USB playback/USB display/	
Contware Compatible	WiFi display)	Yes
	Multiple display administrator	Yes
Number	UPC code	8400460-3094-0
	BenQ Part Number	9H.F0YTM.NE2
Warranty	Warranty	3-Year on site
Features	•	Control Daisy Chain, ID Setting, Sharpness Enhancement, Proof
i catures		tive Contrast), Picture in Picture (PIP), Picture by Picture (PBP),
	HDMI-HDCP, Scheduling, Ambient Light S	tensor, Internal Temperature Sensor, CEC Control, Freeze/ Blank
	Front I/O, Flicker Free, Low Blue Light	



