

RP702 | Interactive Flat Panel

Features

- 70" Interactive Touch
- Native Full HD 1920 x 1080 Resolution
- 4,000:1 Native Contrast Ratio
- Up to 10 Touch Points
- Android build in
- 6 ms Response Time, MHL

Highlights

Total Eye-Care Solution

The RP702 is designed to safeguard the eye health of teachers and students, preventing eyestrain, eye fatigue and macular degeneration, while ensuring instructional effectiveness.

- Zero-Flicker Technology* for eliminating flickering at all brightness levels
- Low Blue Light Technology* to reduce harmful blue spectrum light emission
- Anti-glare display to reduce reflection for a more legible text and clearer image display

Touch Driver-free

With the RP702's touch driver-free design, teachers just have to plug and play to interact with any content from any supported operating system. No additional installation or setup steps needed.

Multi-Platform Compatibility

Compatible with major operating systems from Windows to Mac, Linux and Chrome, the RP702 is built to work seamlessly with a wide range of computing devices.

10-Point Multi-Touch

With 10-point multi-touch support, teachers and students can interact even more freely with all 10 fingers through a wide array of interactive apps, from creating artworks to playing the piano together.

Front I/O Interface with Protective Cover

Built in the front bezel for easy access, the front I/O interface includes every port needed to support multimedia teaching, from HDMI to touch USB, media USB and OPS USB. It also has an earphone and microphone jack. A protective cover is added to keep away curious hands while giving the IFP a stylish look.

Front Bezel Hotkey Design

Hotkeys are incorporated on the front bezel for quick and easy access to Freeze and Blank features as well as volume and input source control.

Switch Input Source by Touch

Instead of using a remote control, teachers can easily switch between different input sources by touch. It's time-saving and hassle-free.



Specifications

Panel	LCD Size	70"	
	Light Source	LED	
	Active Area (mm)	1549.44 x 871.56mm	
	Resolution	FHD 1920 x 1080 (pixels)	
	Aspect Ratio	16:9	
	Brightness	350 cd/m ² nits (typ.)	
	Contrast Ratio (typ.)	4000:1	
	Response Time (ms)	6ms	
	Pixel Pitch	0.802 mm x 0.802 mm	
	Frame Rate	120 Hz	
	Viewing Angle	178 degree (H) / 178 degree (V)	
	Light Life	50,000 hrs (typ.)	
	Color gamut (x% NTSC)	68%	
Panel Bit	10 bit, 1073.7 M		
Platform Solution	CPU	ARM Cortex A7, 1.2GHz, quad core	
	System Memory	1GB DDR3	
	Storage	4GB	
Power	OS	Android 4.2.2	
	Voltage	100V~240V, 50-60Hz	
	Maximum (Watt)	<220W	
Touch	Standby (Watt)	≤0.5W	
	Power Off (Watt)	≤0.5W	
	Touch points	10 points simultaneously	
Glass	OS supported	Win XP, Win Vista, Win 7, Win 8, Mac 10.6~10.10, Linux, Chrome OS 34.0.1847.134	
	Touch Driver Free	Yes; separated driver for Mac 10.10	
	Tempered glass	4mm (Anti glare 80%)	
	Operation Temp (dC)	0°C ~ 40°C	
	Storage Temp (dC)	-10°C ~ 60°C	
	Storage Humidity	10% ~ 90% RH Non-Condensing	
	Operating Humidity	20% ~ 80% RH Non-Condensing	
	Display Orientation	Landscape/Portrait	
	Usage (hrs/days)	18 hours/days	
	Audio	Audio Input (L/R, RCA)	x1
Audio Output (L/R, RCA)		x1	
Internal Spk		10W x 2	
Line out(3.5mm)		x2	
MIC (3.5mm)		x1	
Line in (3.5mm)		x1	
COAX output		x1	
AC Power	Power (AC) Input	x1	
	Power switch	x1	
I/O	VGA In	x1	
	HDMI Input	x5	
	HDMI Output	x1	
	Composite video In (BNC)	x1(RCA)	
	Composite video Out (BNC)	x1(RCA)	
	Component In (YPbPr, RCA)	x1(RCA)	
	USB port (for USB playback)	x2	
	USB port (PC)	x 2 (for OPS)	
	Control	RS232 Input	x1
		RS232 Output	x1
RJ45 Port		x1	
FW Update		USB / On the air	
OPS/Option board slot		OPS	
ME	Weight (without / with packing)	77 KG/90KG	
	Dimension (WxHxD)	1,625 x 968 x 95mm (Packing) / 1,895 x 1,210 x 340 mm	
	Bezel Width (T/B/L/R)	35/56/35/35 mm	
	Wall Mounting	VESA standard; 400x400 (M8)	
	VESA Hole (for Media Player)	100 x 100 (M4)	
	OPS/Option board slot	Yes	
	Pen Tray	x1	
	Handle	x2	
	Language	OSD	EN/EF/SP/EP/CN/TC/GM/DT/PL/RS/CZ/DN/SW/IT/RM/FN/NG/GK/TK/AB/JP (21L)
		Accessory	X1
Software Compatible	Remote Controller	1.8 meter, detachable, black color. RoHS compliance. Cable length follow BenQ sku list	
	PWR Cord (by region)	Yes (1.5M)	
	VGA Cable	x1	
	Quick start guide	x1 (5M)	
	USB Cable (Touch)	x2	
	Touch Pen (Stylus)	x2	
Embedded OS Number	Multiple Display Administrator	Yes	
	Chalk Board APP	Yes	
	WPS (office viewer APP)	Yes	
Warranty Features	OSD menu with touch enable	Yes	
	UPC Code	840460-3269-2	
Warranty	BenQ Part Number	9H.FIWTK.DA2	
	Warranty	3-year	
Features	Android build in, Image Setting, Digital Daisy Chain, RS232 Control Daisy Chain, Sharpness Enhancement		
	HDMI-HDCP, HDMI-MHL, Freeze/ Blank, Front I/O, Flicker Free, Low Blue Light		

BenQ Canada Corp.

Tel: (416) 363-2367 www.BenQ.ca

BenQ is a registered trademark of BenQ Corp. All rights reserved. Product names, logos, brands, and other trademarks featured or referred to in the material are the property of their respective trademark holders. Specifications subject to change without notice.

RP702 041315_BQ.ca

BenQ

Because it matters