

RP790 | Unique Size Interactive Flat Panel

Features

- 79" Interactive Touch
- Native Full HD 3840 x 2160 Resolution
- 1,400:1 Native Contrast Ratio
- Up to 10 Touch Points
- Android Build In
- 5 ms Response Time, MHL

Highlights

Perfect Size in the Classroom

The RP790, being 98cm in height and 174cm in length, offers a classroom-ready size closest to standard blackboards. So teachers can make the transition to teaching with an interactive flat panel naturally, and schools can save on installation, labor, as well as future maintenance costs.

4K Resolution

With a stunning 4K resolution, the RP790 boasts a pixel density of 55 PPI (Pixels Per Inch), which is three times the PPI of today's mainstream interactive whiteboards in the 77" to 79" size range. Every student in class can now enjoy the highest image clarity.

Total Eye-Care Solution

The RP702 is designed to safeguard the eye health of teachers and students, preventing eyestrain, eye fatigue and muscular degeneration, while ensuring instructional effectiveness.

- Zero-Flicker Technology* for eliminating flickering at all brightness levels
- Low Blue Light Technology* to reduce harmful blue spectrum light emission
- Anti-glare display to reduce reflection for a more legible text and clearer image display

Multi-Platform Compatibility

Compatible with Windows, Mac, Linux and Chrome operating systems, the RP790 works seamlessly with a wide range of computing devices. just plug and play. It's touch driver-free.

Teacher Friendly Front Bezel Design

For uninterrupted teaching, BenQ has build several features into the front bezel for quick and easy access.

- Hotkeys for Freeze and Blank features, as well as volume and input source control
- Multimedia I/O interface that includes every port needed for teaching, from HDMI to Touch USB, media USB and OPS USB ports, and an earphone and microphone jack
- Protective cover to keep away curious hands while giving the IFP a stylish look
- Multi-touch ports including two USB ports, one set on the front bezel, for connecting up to two devices at the same time

Switch Input Source by Touch

Instead of using a remote control, teachers can easily switch between different input sources by touch. It's time-saving and hassle-free.

Custom Android OS for the Classroom

The RP790 features a custom Android OS that comes with various useful apps for classroom instruction, from WPS Office to web Browser, EZWrite and Media Player. This closed platform puts schools in full control over the RP790, ensuring the proper use of the IFP by preventing downloads and use of unauthorized apps. This in turn minimizes unanticipated damages or breakdowns.



Specifications

Panel	LCD Size	79"	
	Light Source	Edge LED	
	Active Area (mm)	1739.52 x 978.48mm	
	Resolution	3840 x 2160 (pixels)	
	Aspect Ratio	16:9	
	Brightness	430cd/m ² nits (typ.)	
	Contrast Ratio (typ.)	1400:1 (typ.)	
	Response Time (ms)	5ms (typ.)	
	Pixel Pitch	0.453 mmx 0.453 mm	
	Frame Rate	120Hz	
	Viewing Angle	178 degree (H) / 178 degree (V)	
	Light Life	30,000 hrs (typ.)	
	Color gamut (x% NTSC)	72%	
Panel Bit	10 bit, 1073.7 M		
Platform Solution	CPU	ARM Cortex A7, 1.2GHz quad core	
	System Memory	1GB DDR3	
	Storage	4GB	
Power	OS	Android 4.2.2	
	Voltage	100 V ~ 240 V, 50-60 Hz	
	Maximum (Watt)	<250W (TBD)	
	Typical (Watt)	No	
	Standby (Watt)	≤0.5W	
Touch	Power Off (Watt)	≤0.5W	
	Touch points	10 points simultaneously	
	OS supported	Win XP, Win Vista, Win 7, Win 8, Mac 10.6~10.10, Linux, Chrome OS 34.0.1847.134	
Glass	OS supported	Win XP, Win Vista, Win 7, Win 8, Mac 10.6~10.10, Linux, Chrome OS 34.0.1847.134	
	Touch Driver Free	Yes; separated driver for Mac 10.10	
	Tempered glass	4mm (Anti glare 80%)	
	Operation Temp (dC)	0°C ~ 40°C	
	Storage Temp (dC)	-10°C ~ 60°C	
	Storage Humidity	10% ~ 90% RH Non-Condensing	
	Operating Humidity	20% ~ 80% RH Non-Condensing	
Display Orientation	Landscape		
Audio	Usage (hrs/days)	18 hours/days	
	Audio Input (L/R, RCA)	x1	
	Audio Output (L/R, RCA)	x1	
	Internal Spk	10W x 2	
	Line out(3.5mm)	x2	
	MIC (3.5mm)	x1	
	Line in (3.5mm)	x1	
	COAX output	x1	
	AC Power	Power (AC) Input	x1
		Power switch	x1
I/O	VGA In	x1	
	HDMI Input	x5 (3 x 1080P; 2 x 4K2K)	
	HDMI Output	x1	
	Composite video In (BNC)	x1(RCA)	
	Composite video Out (BNC)	x1(RCA)	
	Component In (YPbPr, RCA)	x1(RCA)	
	USB port (for USB playback)	x2	
	USB port (PC)	x 2 (for OPS)	
	Control	RS232 Input	x1
	Control	RS232 Output	x1
ME	Control	RJ45 Port	x1
	FW Update	USB / On the air	
	OPS/Option board slot	OPS	
	Weight (without / with packing)	Weight (without / with packing)	91kg/112kg
		Dimension (WxHxD)	1847 x 1093 x 95 mm / 2115 x 1400 x 360 mm
	Bezel Width (T/B/L/R)	35/56/35/35 mm	
	Wall Mounting	VESA standard; 600x400 (M8)	
	VESA Hole (for Media Player)	100 x 100 (M4)	
	OPS/Option board slot	Yes	
	Pen Tray	x1	
Handle	x4		
Language	OSD	EN/EF/SP/EP/CN/TC/GM/DT/PL/RS/CZ/DN/SW/IT/RM/FN/NG/GK/TK/AB/JP (21L)	
	Accessory	Remote Controller	X1
Accessory	PWR Cord (by region)	1.8 meter, detachable, black color. RoHS compliance. Cable length follow BenQ sku list	
	VGA Cable	Yes(1.5M)	
	Quick start guide	x1	
	USB Cable (Touch)	x1 (5M)	
	Touch Pen (Stylus)	x2	
Software	Multiple Display Administrator	Yes	
	Compatible	Chalk Board APP	Yes
	Compatible	WPS (office viewer APP)	Yes
Embedded OS Number	OSD menu with touch enable	Yes	
	UPC Code	8400460-3246-3	
Warranty	BenQ Part Number	9H.F1VTK.DE2	
	Warranty	3-year	
Features	Android build in, Image Setting, Digital Daisy Chain, RS232 Control Daisy Chain, Sharpness Enhancement		
	HDMI-HDCP, HDMI-MHL, Freeze/ Blank, Front I/O, Flicker Free, Low Blue Light		

BenQ Canada Corp.

Tel: (416) 363-2367 www.BenQ.ca

BenQ is a registered trademark of BenQ Corp. All rights reserved. Product names, logos, brands, and other trademarks featured or referred to in the materials are the property of their respective trademark holders. Specifications subject to change without notice.

RP790 030515_BQca

BenQ

Because it matters