INTERACTIVE TAT PANEL TATE











Highlights

Interactive displays have become one of the most powerful office tools today, replacing traditional meetings and trainings with a new style of business communication that's proven to enhance meeting efficiency, training effectiveness, collaborative discussion, and team building. A winning solution for your business, the BenQ Interactive Flat Panel T420 combines the power of optical touch panel and multimedia connectivity to maximize your presentations. Designed with safety and flexibility in mind, the T420 is easy and simple to install in any office setting using a VESA wall mount.



Optical Sensing Touch Technology

Built with the Optical Sensing Touch technology, the T240 allows you to control your computer directly by touching the screen. It's faster, easier and far more precise when all you need to do is point and touch with the tip of your finger. Connect your computer to the T420 with a USB cable to get started!



Optical Dual Touch Technology

Pair the T420 with Windows® 8 / Windows® 7 and watch the Optical Dual Touch Technology works its magic turning the displayed image or spreadsheet figure into a multi-touch screen. Trainer or speaker can invite two audiences to come up to the board for a quick contest and trial.



Ambient Light Sensor

The T420 is built with an ambient light sensor to detect the amount of ambient lighting in its surrounding and adjust the display setting accordingly without user intervention. This means the audience can always enjoy optimal picture quality in office.



Integrated Speaker

To help professional elites gain the competitive edge by enriching their meeting with multimedia resources, BenQ has built 12W speakers into the T420. The use of videos, music and sound effects make every presentation more engaging and effective.



Specifications	
<u> </u>	
LCD Size	42"
Light Source	CCFL
Resolution	FHD 1920 x 1080
Aspect Ratio	16:9
Brightness (typ)	440 nits
Contrast Ratio (typ)	1500:1
Response Time (ms)	5ms
Frame Rate	60Hz
Viewing Angle (L/R: U/D)	178/178
Color gamut (x% NTSC)	72%
Panel Bit	10 Bit
Weight (lb) without packing/with packing	67.24 / 71.65 lb
Dimension (WxHxD inch)	40" x 23" x 5.1"
Housing Material	Metal (NCT)
Wall Mounting (inch)	4 Holes (15.74" x 7.87")
Power	
Voltage	100 V - 240V, 50 Hz / 60 Hz (built-in)
Maximum (Watt)	<210W
Standby (Watt)	<0.5W
Touch	
Technology	Dual Touch - Windows 7 & Windows 8.
	Single Touch - Windows XP, Windows Vista & MAC
Resolution (Points area function)	32767 x 32767
Capacity	2 simultaneous touches
Touch Output	USB 2.0
PC	Support Windows XP, Windows Vista, Win 8 / Win 7
Accuracy	+/- 5mm over 95% of touchable area
Audio	
Audio W (Amp)	12W x 2
	1244 X 2
IO (Amp)	12W X 2
IO Line in	Yes
IO Line in Power (AC) Input / Output	
IO Line in Power (AC) Input / Output Audio Output (L/R, RCA)	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R)	Yes Yes Yes Yes Yes
IO Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R)	Yes (x2)
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In	Yes Yes Yes Yes Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input	Yes (x2)
IO Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out	Yes Yes Yes Yes Yes Yes Yes Yes Yes (x2) Yes
IO Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out USB (Touch to External PC)	Yes
IO Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out	Yes
IO Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA)	Yes
IO Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC)	Yes
IO Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Features	Yes
IO Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Features Sharpness Enhancement	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Features Sharpness Enhancement Proof of Image Retention	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Features Sharpness Enhancement Proof of Image Retention DCR	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP)	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP) De-Interlacing / Comb Filter	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP) De-Interlacing / Comb Filter Color Processing	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP) De-Interlacing / Comb Filter Color Processing Build-In Video Wall Support	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP) De-Interlacing / Comb Filter Color Processing Build-In Video Wall Support Scheduling	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP) De-Interlacing / Comb Filter Color Processing Build-In Video Wall Support Scheduling Ambient Light Sensor	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP) De-Interlacing / Comb Filter Color Processing Build-In Video Wall Support Scheduling Ambient Light Sensor Total Turn-on Time	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP) De-Interlacing / Comb Filter Color Processing Build-In Video Wall Support Scheduling Ambient Light Sensor Total Turn-on Time Diagnostic DC Voltage	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP) De-Interlacing / Comb Filter Color Processing Build-In Video Wall Support Scheduling Ambient Light Sensor Total Turn-on Time Diagnostic DC Voltage Internal Temperature Sensor	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP) De-Interlacing / Comb Filter Color Processing Build-In Video Wall Support Scheduling Ambient Light Sensor Total Turn-on Time Diagnostic DC Voltage Internal Temperature Sensor Limited Warranty	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP) De-Interlacing / Comb Filter Color Processing Build-In Video Wall Support Scheduling Ambient Light Sensor Total Turn-on Time Diagnostic DC Voltage Internal Temperature Sensor	Yes

T420 02-13-13-BQca



