INTERACTIVE TL650 **FLAT PANEL**











Highlights

Interactive displays have become one of the most powerful office tools today, replacing traditional meetings and trainings with a new style of business communication that's proven to enhance meeting efficiency, training effectiveness, collaborative discussion, and team building. A winning solution for your business, the BenQ Interactive Flat Panel T650 combines the power of optical touch panel and multimedia connectivity to maximize your presentations. Designed with safety and flexibility in mind, the T650 is easy and simple to install in any office setting using a VESA wall mount.



Optical Sensing Touch Technology

Built with the Optical Sensing Touch technology, the T650 allows you to control your computer directly by touching the screen. It's faster, easier and far more precise when all you need to do is point and touch with the tip of your finger. Connect your computer to the T650 with a USB cable to get started!



Optical Dual Touch Technology

Pair the T650 with Windows® 8 / Windows® 7 and watch the Optical Dual Touch Technology works its magic turning the displayed image or spreadsheet figure into a multi-touch screen. Trainer or speaker can invite two audiences to come up to the board for a quick contest and trial.



Ambient Light Sensor

The T650 is built with an ambient light sensor to detect the amount of ambient lighting in its surrounding and adjust the display setting accordingly without user intervention. This means the audience can always enjoy optimal picture quality in office.



Integrated Speaker

To help professional elites gain the competitive edge by enriching their meeting with multimedia resources, BenQ has built 12W speakers into the T650. The use of videos, music and sound effects make every presentation more engaging and effective.



Specifications	
	GE"
LCD Size	65"
Light Source	Edge LED
Resolution	FHD 1920 x 1080 (pixels)
Aspect Ratio	16:09
Brightness (typ)	360 nits
Contrast Ratio (typ)	4000:1
Response Time (ms)	8ms
Frame Rate	60Hz
Viewing Angle (L/R: U/D)	178/178
Color gamut (x% NTSC)	72%
Panel Bit (8 or 10)	8 bit + FRC (1073.7M)
Weight without packing/with packing	71.5kg / 81.5kg
Dimension (WxHxD)	1515.8 x 888.6 x 114.15mm
Housing Material	Metal (NCT)
Wall Mounting	4 Holes (400 x 400mm)
Power	
Voltage	100 V ~ 240 V, 50/60Hz
Maximum (Watt)	310W
Standby (Watt)	<0.5W
Touch	
Technology	Dual Touch - Windows 7 & Windows 8.
	Single Touch - Windows XP, Windows Vista & MAC
Resolution (Points area function)	32767 x 32767
Capacity Tayob Output	2 simultaneous touches
Touch Output PC	USB 2.0 Supports single touch for Windows XP, Windows
	Vista, Mac, Dual touch for Windows AP, Windows Vista, Mac, Dual touch for Win8 / Win 7
Accuracy	+/- 6mm over 95% of touchable area
Audio	17- Offiliti Over 5570 of toderlable area
Audio W (Amp)	12W x 2
` ','	IIII X Z
IO Line in	
IO Line in	Yes
IO Line in Power (AC) Input / Output	Yes Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA)	Yes Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R)	Yes Yes Yes Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R)	Yes Yes Yes Yes Yes (x2)
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In	Yes Yes Yes Yes Yes Yes Yes Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R)	Yes
IO Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out	Yes
IO Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC)	Yes
IO Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC) RS232 Input \ Output	Yes
IO Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA)	Yes
IO Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC)	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Display Port Input	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Display Port Input RJ45 Port	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Display Port Input	Yes Yes Yes Yes (x2) Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Display Port Input RJ45 Port Features Sharpness Enhancement	Yes Yes Yes Yes (x2) Yes
IO Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Display Port Input RJ45 Port Features	Yes Yes Yes Yes (x2) Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Display Port Input RJ45 Port Features Sharpness Enhancement Proof of Image Retention DCR	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Display Port Input RJ45 Port Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP)	Yes Yes Yes Yes (x2) Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Display Port Input RJ45 Port Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP) De-Interlacing / Comb Filter	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Display Port Input RJ45 Port Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP) De-Interlacing / Comb Filter Color Processing	Yes Yes Yes Yes (x2) Yes Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Display Port Input RJ45 Port Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP) De-Interlacing / Comb Filter Color Processing Build-In Video Wall Support	Yes Yes Yes Yes (x2) Yes 13000:1 Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Display Port Input RJ45 Port Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP) De-Interlacing / Comb Filter Color Processing Build-In Video Wall Support Scheduling	Yes Yes Yes Yes (x2) Yes 13000:1 Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Display Port Input RJ45 Port Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP) De-Interlacing / Comb Filter Color Processing Build-In Video Wall Support Scheduling Ambient Light Sensor	Yes Yes Yes Yes (x2) Yes Yes Yes Yes Yes Yes Yes Yes Yes 13000:1 Yes Yes 10 Bit Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Display Port Input RJ45 Port Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP) De-Interlacing / Comb Filter Color Processing Build-In Video Wall Support Scheduling Ambient Light Sensor Total Turn-on Time	Yes 13000:1 Yes Yes 10 Bit Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Display Port Input RJ45 Port Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP) De-Interlacing / Comb Filter Color Processing Build-In Video Wall Support Scheduling Ambient Light Sensor Total Turn-on Time Diagnostic DC Voltage	Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Display Port Input RJ45 Port Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP) De-Interlacing / Comb Filter Color Processing Build-In Video Wall Support Scheduling Ambient Light Sensor Total Turn-on Time Diagnostic DC Voltage Internal Temperature Sensor	Yes Yes Yes (x2) Yes 13000:1 Yes Yes 10 Bit Yes
Line in Power (AC) Input / Output Audio Output (L/R, RCA) External Speaker Out (L/R) Audio Input (L/R) HDMI In DVI Input \ Output VGA In \ Out USB (Touch to External PC) RS232 Input \ Output Component In (YPbPr, RCA) S-Video In Composite Video In \ Out (BNC) Display Port Input RJ45 Port Features Sharpness Enhancement Proof of Image Retention DCR Picture in Picture (PIP) De-Interlacing / Comb Filter Color Processing Build-In Video Wall Support Scheduling Ambient Light Sensor Total Turn-on Time Diagnostic DC Voltage	Yes

TL650 02-13-13-BQca





