



BenQ DLP Projector

LU9915

Feature High Light

- * 10000lm Laser Light Source
- * 20,000hrs Light Source Life
- * Edge-blending, Corner Fit & Surface Fit
- * Dual Liquid Cooling System
- * HDbaseT



Display

Projection System	DLP 0.67" WUXGA
DMD type	DC3 DMD Chip
Native Resolution	1920x1200 pixels
Brightness	10000 ANSI Lumens
Contrast Ratio*	100,000:1
Display Color	1.07 Billion Colors
Aspect Ratio	Native 16:10 (9 aspect ratio selectable)
Light Source	Laser diodes
Light Source life*(Normal/Eco)	20000/45000 hours

Optical

Throw Ratio	LS1S4 Ultra Short Throw: 0.377
	LS1S3 Wide Fix: 0.76
	LS1S2 Ultra Wide: 0.75 ~ 0.93
	LS1S1 Wide Zoom: 1.25 ~ 1.79
	LS1SD Standard: 1.73 ~ 2.27
	LS1LT1 Semi Long: 2.22 ~ 3.67
	LS1LT2 Long Zoom1: 3.58 ~ 5.38
	LS1LT3 Long Zoom2: 5.31 ~ 8.26
	LS1S4 Ultra Short Throw: Fixed
	LS1S3 Wide Fix: Fixed
Zoom Ratio	LS1S2 Ultra Wide: 1.25X
	LS1S1 Wide Zoom: 1.41X
	LS1SD Standard: 1.3X
	LS1LT1 Semi Long: 1.65X
Lens Control	LS1LT2 Long Zoom1: 1.5X
	LS1LT3 Long Zoom2: 1.55X
	8 Lens (Motorized Zoom and Focus)
	Vertical: 0% ~ 50%
Lens shift	Horizontal: -10%~10%, Standard Lens
	for further information, please refer to the Lens Information
Keystone Correction	Vertical: ± 30 degrees, Horizontal: ± 30 degrees
Projection Offset	NA
Projection Size	50" ~ 500", Standard Lens

Audio

Built-in Speaker	NA
------------------	----

Special Feature

Security(防盜為主) Feature	Security Bar, Power Cord Lock Custom Lightsource Mode (light power adjustment), Dicom Simulation Mode, 2D Keystone, Blank to True Black, Edge-blending, Geometric Correction, 3D Sync, 24/7 Hours Operating, Dust Proof Engine, Dual Liquid Cooling System, Auto High Altitude Mode, 360 Degree & Portrait Projection.
---------------------------	---

Compatibility

Resolution Support	VGA(640 x 480) to WUXGA(1920 x 1200)
Horizontal Frequency	15K - 92kHz
Vertical Scan Rate	23 - 85Hz
HDTV/UHDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM

Power

Power Consumption(Normal)	1290W@100V, 1215W@240V (Typical)
Standby Power Consumption	Normal < 0.5W, Network < 6W.
Power Supply	100 ~ 240V AC

Dimension and Weight

Product Dimensions (WxHxD)	500 X 211 X 583 mm
Product Weight	28 kg

Operation Condition

Noise Level(Normal/Eco)	42/39 dBA
Operating Temperature	0 ~ 45°C

Accessories

Accessories (Standard)	Power Cord Remote Control VGA cable(1.8m) Wired Remote Cable Anti-Theft Screw Lens Hole Cap Installation Guide Regulatory Statement
Accessories (Optional)	LS1S4 Ultra Short Throw(SJ.JCY37.001) LS1S3 Wide Fix(SJ.JAM37.011) LS1S2 Ultra Wide (SJ.JAM37.061) LS1S1 Wide Zoom(SJ.JAM37.021) LS1SD Standard(SJ.JAM37.001) LS1LT1 Semi Long(SJ.JAM37.051) LS1LT2 Long Zoom1(SJ.JAM37.031) LS1LT3 Long Zoom2(SJ.JAM37.041)

OSD

On Screen Display Language	English/ French/ German/Italian/ Japanese/ Korean/ Portuguese/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Traditional Chinese (12 Languages)
----------------------------	--

Notice

* The Contrast is measure by Full On Full Off standard.

*LightSource life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.





Connectivity




- | | | | | | |
|---|----------|---|--------------------|----------|---|
| 1 HDMI | Quantity | 1 | 11 3D Sync out | Quantity | 1 |
| 2 DisplayPort | | 1 | 12 3D Sync In | | 1 |
| 3 DVI-D In | | 1 | 13 Wired Remote In | | 1 |
| 4 Computer In-1 (D-sub 15pin, Female) | | 1 | 14 12V Trigger | | 1 |
| 5 Computer In-2 (5BNC, YBPBR) | | 1 | | | |
| 6 Monitor out (D-sub 15pin, Female) | | 1 | | | |
| 7 3G-SDI In | | 1 | | | |
| 8 3G-SDI Out | | 1 | | | |
| 9 HDBaseT(RJ45 for Video Display and Network control) | | 1 | | | |
| 10 RS232 In (D-sub 9pin, male) | | 1 | | | |

Installation




Screen Size	SJAM17.011			SJAM17.021			SJAM17.001			SJAM17.051									
	Wide Fix Lens			Wide Zoom Lens			STD Lens			Semi long Zoom1									
Diagonal	Width	Height (B)	Distance (A)																
			Fixed	Wide	Tele	Wide	Tele	Wide	Tele	Wide	Tele								
40	1.02	34	0.86	21	0.54	25.1	0.84	41.4	1.05	59.9	1.52	97.2	1.45	75.8	1.93	73.6	1.87	124.1	3.15
50	1.27	42	1.08	26	0.67	31.5	0.81	52.3	1.33	75.9	1.92	120.1	1.63	95.5	2.42	92.9	2.36	155.9	3.96
60	1.52	51	1.29	32	0.81	38.5	0.96	63.1	1.60	90.9	2.31	147.1	2.21	115.1	2.92	112.1	2.85	187.8	4.77
80	2.03	68	1.72	42	1.08	52.0	1.32	84.9	2.16	121.8	3.09	117.0	2.97	154.3	3.92	150.5	3.82	251.4	6.39
100	2.54	85	2.15	53	1.35	65.5	1.68	108.6	2.71	152.7	3.98	147.0	3.73	193.5	4.92	188.9	4.80	315.0	8.00
120	3.05	102	2.58	64	1.62	78.9	2.01	128.4	3.26	183.6	4.66	176.9	4.49	232.6	5.91	227.6	5.79	378.6	9.62
150	3.81	127	3.23	79	2.02	99.1	2.52	161.0	4.09	230.0	5.84	221.8	5.63	291.6	7.41	285.0	7.24	474.1	12.04
180	4.57	153	3.88	95	2.42	119.3	3.03	183.6	4.92	276.4	7.02	280.7	6.77	350.5	8.90	342.6	8.70	585.5	14.47
200	5.08	170	4.31	106	2.69	132.8	3.37	215.3	5.47	307.3	7.81	296.6	7.53	389.7	9.90	381.0	9.68	633.1	16.08
300	7.62	254	6.46	159	4.04	200.1	5.08	324.0	8.23	481.9	11.73	446.3	11.34	585.9	14.9	573.2	14.56	951.2	24.16
400	10.16	339	8.62	212	5.38	267.4	6.79	432.7	10.99	616.6	15.66	595.9	15.14	782.3	19.87	765.3	19.44	1269.7	32.25
500	12.70	424	10.77	265	6.73	334.3	8.50	541.5	13.75	771.2	18.59	745.6	18.94	976.3	24.85	957.4	24.32	1587.8	40.33


6-CEILING MOUNT HOLE
M4*0.7 SCREW L=16 mm (MAX.)



Screen Size	SJAM17.011			SJAM17.041			SJAM17.061										
	Long Zoom 1 Lens			Long zoom 2 Lens			Ultra Wide zoom Lens										
Diagonal	Width (C)	Height (B)	Distance (A)														
			Wide	Tele	Wide	Tele	Wide	Tele	Wide	Tele							
40	1.02	34	0.86	21	0.54	116.7	3.01	181.0	4.60	173.9	4.42	277.7	7.05	24.5	0.62	31.1	0.79
50	1.27	42	1.08	26	0.67	146.7	3.80	227.6	5.78	220.2	5.59	360.0	8.89	31.1	0.79	39.2	1.00
60	1.52	51	1.29	32	0.81	180.7	4.59	274.1	6.96	266.6	6.77	422.3	10.73	37.6	0.96	47.4	1.20
80	2.03	68	1.72	42	1.08	242.7	6.16	367.3	9.33	358.4	8.13	567.0	14.40	50.8	1.29	63.8	1.62
100	2.54	85	2.15	53	1.35	304.3	7.73	460.4	11.70	452.1	11.48	711.6	18.07	63.9	1.62	80.2	2.04
120	3.05	102	2.58	64	1.62	366.7	9.31	533.6	14.06	544.9	13.94	866.2	21.75	77.1	1.96	96.6	2.45
150	3.81	127	3.23	79	2.02	459.4	11.67	693.3	17.61	684.0	17.37	1073.1	27.26	86.8	2.46	121.1	3.08
180	4.57	153	3.88	95	2.42	552.4	14.03	833.0	21.16	823.1	20.91	1290.1	32.77	116.5	2.96	145.7	3.70
200	5.08	170	4.31	106	2.69	614.7	15.6	925.4	23.53	915.9	23.26	1434.7	36.44	139.7	3.29	162.1	4.12
300	7.62	254	6.46	159	4.04	924.0	23.47	1380.1	35.36	1379.6	35.04	2157.8	54.81	196.4	4.96	244.0	6.26
400	10.16	339	8.62	212	5.38	1233.9	31.34	1857.9	47.19	1843.3	46.82	2880.9	73.18	261.2	6.63	325.9	8.28
500	12.70	424	10.77	265	6.73	1543.7	39.21	2323.3	59.02	2307.1	58.60	3604.0	91.54	326.9	8.30	407.7	10.36



Screen size	SJJCY17.001														
	Ultra Short Reflection														
Diagonal	Width	Height	H1	H2	L1	L2	L3								
inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
100	2540	85	2166	53	1355	19	485	28	701	33	849	22	564	-1	-24
120	3048	102	2599	64	1627	23	596	32	812	39	1000	28	715	5	127
150	3810	128	3247	80	2032	30	763	39	979	48	1227	37	942	14	354
200	5080	170	4330	107	2711	41	1041	49	1257	63	1606	52	1321	29	733
250	6350	213	5415	133	3391	52	1320	60	1536	78	1984	67	1699	44	1111
300	7620	256	6500	160	4071	63	1598	71	1814	93	2362	82	2077	59	1489
350	8890	299	7585	187	4752	74	1877	82	2093	108	2741	97	2456	74	1868



- L1: Screen to the point of mirror
- L2: Screen to projector front
- L3: Screen to project back
- H1: Screen bottom to projector top side
- H2: Screen bottom to projector bottom

Logo & Certification

