MX507

Projection System	DLP
Native Resolution	XGA (1024 x 768)
Brightness*	3200 lumens
Contrast Ratio	13000:1
Display Color	1.07 Billion Colors
Lens	F=2.56-2.68, f=22.04-24.14mm
Aspect Ratio	Native 4:3 (5 aspect ratio selectable)
Throw Ratio	1.96-2.15 (78" @ 3.1m)
Image Size (Diagonal)	60"-180"/ 300' (Clear Focus/ Maximum)
Zoom Ratio	I.I:I (Powered)
Keystone Adjustment	ID, Vertical +/- 40 degrees
Projection Offset	120% ±5%
Resolution Support	VGA (640 x 480) to UXGA (1600 x 1200)
	15K-102KHz
Horizontal Frequency	
Vertical Scan Rate	23-120Hz
	Computer In (D-sub I5pin) x 2 (Share with component)
	Monitor Out (D-sub I5pin) x I
	Composite Video In (RCA) x I
	S-Video In (Mini DIN 4pin) x I
Interface	Audio In (Mini Jack) × I
	Audio Out (Mini Jack) × I
	Speaker 2W x I
	USB (Type mini B) x I (Download & Page/down)
	RS232 (DB-9pin) x I
	IR Receiver x I (Front)
Dimensions(W x H x D)	283 x 95 x 222mm (include feet)
	283 x 88.7 x 222mm (exclude feet)
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM
Weight	1.8kg
Audible Noise	33/ 28 dBA (Normal/ Economic mode)
Power Supply	AC100 to 240V, 50 to 60Hz
Power Consumption	Normal 270W, Eco 220W, Standby < 0.5W
	Arabic/ Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/
On-Screen Display	Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/
Languages	Romanian/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28
	Languages)
Picture Modes	Dynamic/ Presentation/ sRGB/ Cinema/ User I/ User 2
	Remote Control w/ Battery
	Power Cord (by region)
Accessories (Standard)	Quick Start Guide
	Warranty Card (by region)
	VGA (D-sub I5pin) Cable
	Spare Lamp Kit
Accessories (Optional)	Ceiling Mount
Accessories (Optional)	3D Glasses
	Carry Bag
	Frame Sequential: Up to 720p 60Hx (Video), Up to WXGA I20Hz (PC
3D Support and	Timing)
Compatibility	Side by Side: Up to 1680 x 1050 60Hz (PC Timing)
	Top Bottom: Up to 1680 x 1050 60Hz (PC Timing)