

BenQ

MX710/711

Digital Projector



HIGHLIGHTS

- Microphone in with 10W speaker x 1
- USB reader
- USB Display (Plug-n-Play)
- LAN Display
- 4-1 Display
- Remote Desktop
- Wireless Display (Optional)
- Filter Free Design
- No Color Decay
- Crestron RoomView compatible
- PJ-Link compatible
- 2700/3200 ANSI Lumens
- XGA Native Resolution
- BrilliantColor™
- 3D Color Management
- VIDI™
- Vertical Auto Keystone
- Keystone ± 40 Degree
- 6 Segment color wheel
- Variable Audio Out
- Closed Captioning

Projection System	DLP® technology by Texas Instruments®	
Native Resolution	XGA (1024 x 768)	
Brightness	2700/3200 ANSI lumens	
Contrast Ratio	5000:1 (Full on/Full off)	
Keystone	Auto Keystone Vertical ± 40 Degree; Manual Vertical ± 40 Degree	
Aspect Ratio	4:3 Native (5 selectable aspect ratio)	
Color	Full 16.7 million color palette	
Lens	F=2.59~2.87	
Zoom Ratio	Manual Zoom, 1.3:1	
Image Size (Diagonal)	32" to 300"	
Throw Ratio	1.5 to 1.95(65"@2M)	
Lamp	210W, 4000/5000 hrs ; 230W 3500/5000hrs(Normal/Economic mode)	
Computer Compatibility	VGA(640 x 480) to UXGA (1600x1200)	
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	
Video Compatibility	NTSC, PAL, SECAM	
Horizontal Frequency	31-99 kHz	
Vertical Scan Rate	48-120 Hz	
Input Terminals	PC	Analog RGB: D-sub 15 pin x 2
		LAN Networking: RJ-45 x1 (LAN Display)
		USB connector: Type A x 1 (USB thumb drive) USB Type mini B x1 (USB display)
	A/V	HDMI V1.3 x 1
		S-Video: Mini Din 4 pin x 1 Composite Video: RCA x 1
	Audio	Audio L/R : RCA x 1 Stereo Mini Jack x 1
Output Terminals	PC	D-sub 15 pin x 1 Variable Audio Out : Stereo Mini Jack x 1 12 V Trigger x 1
		Audio
	Control Terminal	Serial Connector : RS232 x 1 RJ45 x 1 USB mini Type B x 1(Page up/down) shared
Dimensions(W x H x D)	290mm x 102.97mm x 236.1mm	
Weight	5.8 lbs (<2.65kg)	
Power Supply	100 to 240 VAC, 50/60 Hz	
Power Consumption	300W/ 320W, Standby < 1W	
Audible Noise	31/27 dB; 33/28dB (Normal/Economic mode)	
On-Screen Display Languages	Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hungarian/ Indonesian/ Italian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (26 Languages)	
Picture Modes	PC Input:	A/V Input :
	Dynamic Mode	Dynamic Mode
	Presentation Mode	Presentation Mode
	sRGB Mode	sRGB Mode
	Cinema Mode	Cinema Mode
	User 1 Mode	User 1 Mode
User 2 Mode	User 2 Mode	
Functions	BrilliantColor™	Blank
	VIDI™	Panel Key Lock
	3D Color Management	Auto Off
	Crestron LAN Control	Security Password
	Closed Captioning	HDTV Compatible
	Digital Zoom (x2)	High Altitude Mode
	Variable Audio Out	"Q?" Hot Key for FAQ
	Quick Cooling	3D Ready
	Quick Auto Search	Freeze
	Quick Start Guide	VGA(D-sub) cable
Accessories (Standard)	Manual CD	Power cord
	Remote control w/battery	Soft carry case
	Presentation Plus	Spare Lamp Kit
Accessories (Optional)	RS232 Cable	