



65" Interactive Flat Panel Display RP653

Light Source LED

Voltage 100V ~ 240V, 50Hz / 60Hz

Maximun (Watt) 211W

Technology IR Touch

Touch interface Touch Interface

OS Supported Windows XP, Windows Vista, Windows 7, Windows 8, Windows 10, Mac OS X 10.6 to 10.11, Linux, Chrome OS

Resolution (points area function) 32,767 x 32,767

Tempered glass 4mm, tempered glass

NOT Up to 20 points

AG coating 80%

CO Yes

MIC N/A

LI Yes (x3 3.5mm, along with 3VGA input)

E Yes

ESO N/A

AO N/A

AI Yes (x1; L/R, in mini CVBS)

IS 10W x 2

I/O Connection

Pen Tray N/A

Ha Yes (x2)

WM VESA Standard; 600 x 400

DWHD 1,523 x 924 x 98mm / 1,697 x 1,071 x 220mm

PS Yes

PO N/A

PI Yes

OPSS N/A

HDMIO N/A

HDMII HDMI 1.3 (x 3; MHLx1)

VGAO Yes

VGAI Yes (x3)

UPUE N/A

UP Yes (x4; USB2.0x3; USB3.0x1)

SVI N/A

CI N/A

CVO N/A

CVI Yes (RCA, share with mini CVBS)

FU USB / OTA
 RJ45Port Yes
 RO N/A
 RI Yes
 NFC Yes
 SLC Yes
 TP NFCPen x2
 TUC Yes
 UMEF Yes
 QSG Yes
 VGAC Yes
 AC Yes
 PCBR Yes (x4; EU, UK, US, AU)
 RC Yes
 Front I/O Cover Yes
 Weight (kg) (without packing/with packing) 46kg / 57kg
 Display Orientation Landscape
 AG Yes
 VESA Hole (For Media Player) N/A
 LS 65"
 RP FHD 1920 x 1080
 BT 350 nits
 CRT 1,400:1
 RT 6ms
 CG 72%
 PB 8 bit
 LLT 30,000hrs
 VAHV 178° / 178°



AG+ Screen

