

Model Name

MW632ST Digital Projector

Unique selling point

- * SmartEco Power Saving technology
- * Up to 10000hours Long lamp life * 2 HDMI Ports and 1 MHL
- * <0.5W standby mode
- * Short Throw Ratio










Projection System	DLP						
Native Resolution	WXGA (1280x800)						
Brightness	3200AL						
Contrast Ratio	13000:1						
Display Color	1.07 Billion Colors						
Lens	F/#=2.6~2.78 f=10.2~12.24						
Aspect Ratio	Native 16:10 (5 aspect ratio selectable)						
Throw Ratio	0.72~0.87(87"±3% @ 1.36m)						
Image Size (Clear Focus/ Maximum)	60"~120" / 300"						
Zoom Ratio	1.2:1						
Lamp Type	196W						
Lamp(Normal/Economic/SmartEco Mode)*	4000/6000/6500/10000 hours						
Keystone Adjustment	ID, Vertical +/- 30 degrees						
Projection Offset	105% ±5%						
Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200) * RB= Reduced blanking					
Horizontal Frequency	15K~102KHz						
Vertical Scan Rate	24~120Hz						
Compatibility	HDTV Compatibility	480i, 480p, 576i, 576p	, 720p, 1080i, 1080p				
• •	Video Compatibility	NTSC, PAL, SECAM	•				
	3D Compatibility	PC: 120Hz Frame Se	equential 3D for resolutions up to WXGA, PC: 60Hz Top-bottom 3D for				
Interface	Computer in (D-sub 15pin)	resolutions up to SXC x I (Share with compo					
	Monitor out (D-sub 15pin)	x I					
	Composite Video in (RCA)	хI					
	S-Video in (Mini DIN 4pin) x I						
	HDMI (1.4a) x2 (one share with MHL2.0)						
	Audio in (Mini Jack) x I						
	Audio L/R in (RCA) x I						
	Audio out (Mini Jack) x I						
	Speaker	x I 10W x I					
	'						
	USB (Type A) x I (1.5A power supply) RS232 (DB-9pin) x I						
	IR Receiver		x I				
Dimensions	Dimensions(W x H x D)		x2 (Front+Top) 287.3 x 114.4x 232.6 mm				
Dimensions	Weight	2.6KG	5 111111				
Power	Power Supply	AC100 to 240 V, 50 t	o 60 Hz				
	Power Consumption	Normal 305W. Eco 2	20W. Standby <0.5W				
	Power Management Function	Automatic power off	Automatic power off after 20 minutes without a display source.				
	2200 404 (41						
Audible Noise	33/28 dBA (Normal/Economic mode)						
On-Screen Display Languages		Arabic/ Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages)					
Picture Modes	**Bright / Presentation / sRGB / Cinema / (3D) / User I / User 2					
Accessories	Standard	Optional					
	Remote Control w/ Battery	Presentation Plus	P/N: 65.J9306.002				
	Power Cord (by region)	Spare Lamp Kit	P/N: 5J.JAR05.001				
	User Manual CD	Ceilling Mount	P/N: 5J.J2K01.001				
	Quick Start Guide	3D Glasses	P/N: 5J.J9H25.001				
	Warranty Card (by region)	Carry bag					
	VGA(D-sub 15pin) Cable	and the contract of the contra					

*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.


^{**} Default mode is **Presentation**. When 3D is on, Picture Modes only shows 3D. When 3D is off, it is not shown in Picture Modes.


Distance Chart


Screen size			Distance from screen (mm)				
Diagonal		w		Min length		Max length (min. zoom)	Vertical offset (mm)
Inch	mm	(mm)	H (mm)	(max. zoom)			
40	1016	862	538	625	688	750	13
60	1524	1292	808	938	1031	1125	20
80	2032	1723	1077	1250	1375	1500	27
100	2540	2154	1346	1563	1719	1875	34
120	3048	2585	1615	1875	2063	2250	40
140	3556	3015	1885	2188	2406	2625	47
160	4064	3446	2154	2500	2750	3000	54
180	4572	3877	2423	2813	3094	3375	61
200	5080	4308	2692	3125	3438	3750	67
250	6350	5385	3365	3906	4297	4688	84
300	7620	6462	4039	4688	5156	5625	101



Wall mount/Ceiling mount Chart







Dimension







