

Model Name

Unique selling point

- * SmartEco power saving technology
 * Native Full HD high resolution
- * Blu-ray 3D supported

Trade Mark






Projection System	DLP						
Native Resolution	Full HD (1920×1080)						
Brightness	3000AL						
Contrast Ratio	10000:1						
Display Color	1.07 Billion Colors						
Lens	F=2.6-2.7 f=10.2-11.22 mm						
Aspect Ratio	Native 16:9 (5 aspect ratio selectable)						
Throw Ratio	0.69~0.76(65.7"±3% @ lm)						
Image Size (Diagonal)	60"~300"						
Zoom Ratio	I.I: I						
Lamp Type	210W						
Lamp Mode (Normal/Economic/SmartEco)	4000/6000/8000 hours						
Keystone Adjustment	ID, Vertical +/- 40 degrees						
Projection Offset	105% ±5%						
Resolution Support	VGA(640 x 480) to WUXGA_	RB(1920X1200) *RB=Reduce	d blanking				
Horizontal Frequency	15~102KHz		-				
Vertical Scan Rate	23~120Hz						
Compatibility	HDTV Compatibility 480i, 480p, 576i, 576p, 720p, 1080i, 1080p						
,,,,,	Video Compatibility NTSC, PAL, SECAM						
	3D Compatibility	Frame Sequential: Up to 72	Op.				
	(Please refer to User's Manual						
	for detailed support timing.)	Side by Side: Up to 1080i/p					
		Top Bottom: Up to 1080p					
Interface	Computer in (D-sub 15pin)		x l				
interface	Monitor out (D-sub 15pin)		x l				
	Composite Video in (RCA)		x l				
			x l				
	S-Video in (Mini DIN 4pin)						
	HDMI		хI				
	Audio in (Mini Jack)		x I				
	Audio out (Mini Jack)		x I				
	Speaker		x I (I0W)				
	USB (Type Mini B)		x I				
	RS232 (DB-9pin)		x I				
Dimensions	Dimensions(W x H x D)		311.8 x 104.7 x 247.5 mm (with feet)				
			$311.8 \times 94.7 \times 247.5$ mm (without feet)				
	Weight		2.8kg(6.39 lbs)				
Power	Power Supply		AC100 to 240 V, 50 to 60 Hz				
	Power Consumption		Normal 280W, Eco 230W, Standby <0.5W				
Audible Noise	36/33 dBA (Normal/Economic	mode)					
On-Screen Display Languages	Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages)						
Picture Modes	Dynamic/Presentation/sRGB/C	Cinema/(3D)/User 1/User 2					
Accessories	Standard		Optional				
	Lens Cover		Spare Lamp Kit				
	Remote Control w/ Battery		Wall Mount				
	Power Cord (by region)		Carry bag				
	User Manual CD		3D Glasses				
	Quick Start Guide						
	Warranty Card (by region)						
	VGA(D-sub 15pin) Cable						
	. z. (o suo ropin) cubie						

TH682ST Digital Projector

Distance Chart

Installation for a 16:9 ratio screen




The screen aspect ratio is 16:9 and the projected picture is in a 16:9 aspect ratio

Screen size			Distance from screen (mm)				
Diagonal		M (Н ()	Min length		Max length	Vertical offset
Inch	mm	W (mm)	H (mm)	(max. zoom)	Average	(min. zoom)	(mm)
60	1524	747	1328	913	959	1005	19
70	1778	872	1550	1065	1119	1172	22
80	2032	996	1771	1218	1279	1339	25
90	2286	1121	1992	1370	1438	1507	28
100	2540	1245	2214	1522	1598	1674	31
110	2794	1370	2435	1674	1758	1842	34
120	3048	1494	2657	1826	1918	2009	37

Wall mount/Ceiling mount Chart

Ceiling mount installation



Dimension









⁸Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.