BenQ MS500 Digital Projector

















Display Technology	DLP® by Texas Instruments®	
Native Resolution	SVGA (800 x 600)	
Resolution Supported	VGA (640 x 480) to UXGA (1600 x 1200)	
Brightness	2500 ANSI Lumens	
Contrast Ratio	4000:1 (Full on / Full off)	
Image Size	24" to 300"	
Throw Ratio	1.86 to 2.04 (53" @2M)	
Zoom Ratio	Manual Zoom, 1.10:1	
Keystone correction	1D, vertical +/- 40 degrees	
Lens	F = 2.56 - 2.8, f = 21 - 23.1 mm	
Lamp Life*	220W, 4500 / 5000 hours (Normal / Economic mode)	
Lamp Warranty	12 months or 2,000 cumulative hours whichever comes first	
Operational Noise	33 / 27 dB (Normal / Economic mode)	
Displayable Colours	Full 1.07 billion color palette	
Aspect Ratio	4:3 Native, 5 aspect ratio selectable	
Horizontal Frequency	31 ~ 99 kHz	
Vertical Scan Rate	48 ~ 120 Hz	
vertical Scali Rate	Computer in (D-sub 15pin) x2 (shared with Component )	
Interface	Monitor out (D-sub 15pin) x1	
	Monitor out (D-sub 15pin) x 1 Composite Video in (RCA) x 1	
	S-Video in (Mini DIN 4pin) x 1	
	Audio in (Mini Jack) x 1	
	Audio out (Mini Jack) x 1	
	Speaker 2W x 1  LISP (Type Mini P) x 1 (Download & Page up/down)	
	USB (Type Mini B) x 1 (Download & Page up/down)	
***	RS232 (DB-9pin) x 1	
Video Compatibility	NTSC / PAL / SECAM	
HDTV Compatibility	480i / 480p / 576i / 576p / 720p / 1080i / 1080p	
Dimensions (HxWxD)	287 x 100 x 232 mm	
Weight	Net weight: 2.5 kg.   Gross weight: 3.5 kg.	
Auto Switching Power Supply	100 to 240 VAC, 50/60 Hz	
Power consumption	297W, Standby < 1W	
On Scroon Dienlay Langua	Arabic / Bulgarian / Croatian / Czech / Danish / Dutch / English / Finnish / French / German / Greek / Hindi /	
n Screen Display Languages Hungarian / Indonesian / Italian / Japanese / Korean / Norwegian / Polish / Portuguese / Romanian Simplified Chinese / Spanish / Swedish / Thai / Traditional Chinese / Turkish (28 Languages)		
Application Modes	Dynamic / sRGB / Presentation / Cinema / User 1 / User 2	
Application Wodes	BrilliantColor™	Ouick Auto Search
Functions	Closed Captioning	Wall Color Correction
	3D Color Management	3D Ready
	Digital Zoom (x2)	Blank
	Freeze	Auto Off
	HDTV compatible	
	*	Security Password
	High Altitude Mode	Windows 7 Certified
Accessories Included	Quick Start Guide	VGA Cable
	Manual CD	Power Cord
	Remote Control w/battery	C I IV.
Accessories Optional	Presentation Plus	Spare Lamp Kit
	RS232 Cable	RS232 Cable
	3D Glasses	Soft Carry Case

\* Lamp life results will vary depending on environmental conditions and usage.

All specifications are subject to change without notice.

Available models (specs inc.) may vary from different regions.





