

Data sheet

BenQ MW769

WXGA Data-/ Video projector

- WXGA 1280 x 800
- 4.200 ANSI-Lumens
- 3D via HDMI
- Wireless* /LAN Display
- 1,5x Zoom



144 Hz^o
Triple Flash



Technology	Art. No. / EAN : 9H.JAA77,34E / 471 8755 04794 7 Type : 0,55" DLP™ Native Resolution : WXGA 1280 x 800 Brightness : 4.200 ANSI-Lumens max. Contrast : 13.000:1 Display Color : 1,07 Bil. Aspect Ratio : Physical 16:10 (5 aspect ratio selectable) Cooling system : Front -, Side ventilation, Quick cooling
Lamp	Type : 310 W Lamp life : 2.500h Normal 3.500h Smart Eco Mode Warranty : 12 Months or 2000h
Objectiv	Characteristics : Manual Zoom Image Size (Diagonal) : 0,78 m – 7,62 m Lens : F=2,42 - 2,97, f=20,7 - 31,05 mm Throw ratio : 1,45 – 2,17 m (1,60 m@2 m) Zoom : 1,5:1
Signal	Video Compatibility : NTSC/ PAL/SECAM Video - Modi : 480i, 480p, 576i, 576p, 720p, 1080i, 1080p PC Resolution : VGA (640 x 480) bis UXGA (1600 x 1200) Frequencies H/V : 15-102 kHz, 23-120 Hz Input : Composite Video 1 x RCA Cinch S-Video 1 x Mini Din 4 pin Audio 1 x Stereo Mini Jack / 1x L/R Cinch Microphone 1 x Mini Jack RGB VGA-Analog 2 x D-sub 15 pin (Shared with component) HDMI 2 x HDMI USB 2 x Type A, 1 x Type B, 1 x Type mini B RJ45 1 x LAN Serial input : RS232 1 x D-Sub 9 pin Output : RGB VGA-Analog 1 x D-sub 15 pin Speaker : Audio out 1 x Stereo Mini Jack DC 12 Trigger 1 x 1 x 10 Watt
Control	Functions : Brilliant Color™, VID™, 3D-comb filter, 3-D-Colormanagement, Crestron LAN Control, LAN Display, USB Display, user menu, Presentation - timer, input auto search, Closed Captioning, Key lock, Quick Cooling, Network control, Trapez adjust vertical +/- 30°; horizontal +/- 25°, 5-Segment-Colorwheel, Freeze, PC 3D Ready OSD : 28 Languages Remote : IR-Remote Control Certificates : CE, TÜV-GS
Security Energy	Power Supply : 100-240 VAC, 50/60 Hz Power Consumption : Max. 400 Watt, Eco 340 Watt, Standby <0,5 Watt
Characteristics	Dimensions (W x H x D) : 329 x 137 x 249 mm Weight : 3,90 kg Audible Noise : 36 dB (A) Normal 34 dB (A) ECO-Mode Projection position : Front-, Back-, Table- und Ceiling projection Environment : + 0 ~ + 40°C / 20 ~ 80 % air humidity Standard accessory : Bag, Manual-CD, Remote Control incl. Battery, Power -Cable, Quick Start Guide VGA-Cable, Warranty card Warranty and Service : 36 Month Warranty



* only possible with optional WLAN USB Dongle

