BenQ Digital Camera E605



6 megapixels CCD with 3X opt. zoom

High image resolution with 3X optical zoom lens for you to capture all the details of the image

3D-Rotating lens design

Specially designed 3-Dimension Rotating lens embeds sliding lens technology to achieve thinner camera body.

Shake-Free function supported

Shake-Free is provided in "Sports mode" to avoid blurred images when taking photos.

Large 2.4" TFT LCD

The large color 2.4" TFT display is provided for your clear view every time you take the photos.

BenQ Easy-Dial user interface

BenQ Easy-Dial interface is designed with large icons and texts for you to clearly understand how to operate.

Direct printing mode supported

Easy for you to print photos out directly via the compatible printer (the printer with PictBridge logo) without connecting to the computer first.

PF mode (Pan Focus)

For users who seek an absolute easy-to-shot camera, E605 offers Pan Focus mode for you to take clear photos without focusing first

Quick-Shot

You will not miss any precious moment again because Quick-Shot ensures every immediate snapshot

	Specifications
Image Sensor	6 megapixels effective CCD
Image	2848 x 2144 (6M), 2304 x 1728 (4M), 1600 x
Resolution	1200 (2M), 1280 x 960 (1M), 640 x 480 (VGA)
Lens	Focus Length: F=5.8~17.4mm
	(35mm film equivalent: 35~105mm),
	Aperture: F2.8 / F4.8
Zoom	Optical: 3X / Digital: 4X
LCD	2.37" TFT LCD / 115,000 pixels
Dimensions /	92 x 60 x 24.5 mm /
Weight	135 g (without battery)
Power Source	Rechargeable Lithium-ion Battery
Storage Type	Built-in 32MB (26MB available for usage);
	SD card compatible
Focus Range	Macro: 6 cm
	Normal: 40cm ~ infinity
Shutter Speed	1/2000 ~ 2 sec (4 sec in night scene mode)
Movie Mode	640 x 480 (30fps) pixels; MJPEG
	Continuous recording with sound
White Balance	Auto / Daylight / Cloudy / Tungsten /
	Fluorescent
Exposure	-2~+2 EV (0.3EV / step)
ISO	Auto / 100 / 200 / 400
Flash	Auto / Red eye reduction / Slow Sync /
	Forced flash / Flash off (0.3m ~2m)
Self-Timer	10 sec / 2 sec / 10+2 sec
File Format	Still image: JPEG (EXIF 2.2), DCF
Interface	Digital out: USB2.0
	Audio / Video output (NTSC/PAL)
Accessory	Lithium-ion Battery / USB Cable / AV Cable /
	Camera pouch / Hand strap / User's manual /
	Battery Charger Set / Software CD (AP included)