

BenQ

MP776/777

Digital Projector



HIGHLIGHTS

- Filter Free Design
- No Color Decay
- Crestron LAN Control
- 3500/4000 ANSI Lumens
- XGA Native Resolution
- BrilliantColor™
- 3D Color Management
- VIDI
- 6 Segments Color Wheel
- Auto Keystone
- Keystone ± 40 Degree
- 5W x 2 Speakers
- Variable Audio Out
- Closed Captioning
- HDMI v1.3

Projection System	DLP® technology by Texas Instruments®	
Native Resolution	XGA (1024 x 768)	
Brightness	3500/4000 ANSI lumens	
Contrast Ratio	2600:1 (Full on/Full off)	
Keystone	Auto Keystone Vertical ± 40 Degree; Manual Vertical ± 40 Degree	
Aspect Ratio	4:3 Native, 16:9 Selectable	
Color	Full 16.7 million color palette	
Lens	F=2.56	
Zoom Ratio	Manual Zoom, 1.3:1	
Image Size (Diagonal)	25" to 300"	
Throw Ratio	1.51 to 1.96:1 (65"@2M)	
Lamp	280W, 3000/4000 hours (Normal/Economic mode)	
Computer Compatibility	VGA(640 x 480) to UXGA (1600x1200)	
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080p	
Video Compatibility	NTSC, PAL, SECAM	
Horizontal Frequency	31-93 kHz	
Vertical Scan Rate	48-86 Hz	
Input Terminals	PC	Analog RGB: D-sub 15 pin x 2 HDMI V1.3 x 1
	A/V	S-Video: Mini Din 4 pin x 1 Composite Video: RCA x 1
	Audio	Audio L/R : RCA x 2 Stereo Mini Jack x 1
Output Terminals	PC	D-sub 15 pin x 1 Variable Audio Out : Stereo Mini Jack x 1 12 V Trigger
	Audio	5W x 2
	Control Terminal	Serial Connector : RS232 x 1 RJ45 x 1
Dimensions(W x H x D)	11.4 x 3.7 x 9.9 inch (290 x 94 x 252 mm)	
Weight	7.7 lbs (3.5 kg)	
Power Supply	100 to 240 VAC, 50/60 Hz	
Power Consumption	425W, Standby < 1W	
Audible Noise	34/29 dB (Normal/Economic mode)	
On-Screen Display Languages	Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Hungarian/ Italian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (24 Languages)	
Picture Modes	PC Input:	A/V Input :
	Dynamic Mode	Dynamic Mode
	Presentation Mode	Presentation Mode
	sRGB Mode	sRGB Mode
	Cinema Mode	Cinema Mode
	User 1 Mode	User 1 Mode
	User 2 Mode	User 2 Mode
Functions	BrilliantColor	Freeze
	VIDI	Blank
	3D Color Management	Panel Key Lock
	Crestron LAN Control	Auto Off
	Auto Keystone	Security Password
	Digital Zoom (x2)	HDTV compatible
	Variable Audio Out	High altitude mode
	Quick Cooling	"Q?" Hot Key for FAQ
	Closed Captioning	3D Ready
	Quick Auto Search	
	Quick Start Guide	VGA(D-sub) cable
Accessories (Standard)	Manual CD	Power cord
	Remote control w/battery	Soft carry case
	Presentation Plus	Spare Lamp Kit
Accessories (Optional)	RS232 Cable	

