



Model Name **MX722 Projector**

Unique selling point

- * 4000AL High Brightness
- * 3D Function supported
- * Built-in speakers (10W x 2)
- * <0.5W standby mode
- * Crestron RoomView®, PJ Link and AMX supported
- * LAN control and LAN display function

Trade Mark



Projection System	DLP	
Native Resolution	XGA(1024x768)	
Brightness	4000AL	
Contrast Ratio	5300:1	
Display Color	1.07 Billion Colors	
Lens	F2.59-2.87, f=16.88-21.88mm	
Aspect Ratio	Native 4:3 (5 aspect ratio selectable)	
Throw Ratio	1.51-1.97(65"@ 2m)	
Image Size (Diagonal)	37"~300"	
Zoom Ratio	1.3:1	
Lamp Type	300W	
Lamp(Normal/Economic/SmartEco Mode)*	2000/3000/NA hours	
Keystone Adjustment	1D, Vertical +/- 40 degrees	
Projection Offset	115%±5%	
Resolution Support	VGA(640 x 480) to UXGA(1600 x 1200)	
Horizontal Frequency	15-102KHz	
Vertical Scan Rate	23-120Hz	
Compatibility	HDTV Compatibility	480i, 480p, 576i, 567p, 720p, 1080i, 1080p
	Video Compatibility	NTSC, PAL, SECAM
Interface	Computer in (D-sub 15pin)	x 2(Share with component)
	Monitor out (D-sub 15pin)	x 1
	Composite Video in (RCA)	x 1
	S-Video in (Mini DIN 4pin)	x 1
	HDMI	x1
	Audio in (Mini Jack)	x 2
	Audio in (L/R)	x1
	Audio out (Mini Jack)	x 1
	Microphone in (Mini Jack)	x 1
	Speaker	10W x 2
	USB (Type mini B)	x1 (Download & page/down)
	RJ45	x 1 (LAN Control & LAN Display)
	RS232 (DB-9pin)	x 1
	DC 12V Trigger (3.5mm Jack)	x 1
	IR Receiver	x2 (Front+rear)
Dimensions	Dimensions(W x H x D)	339 x 120.5 x 238 mm
	Weight	3.8kg(8.4lbs)
Power	Power Supply	AC100 to 240V, 4.5A, 50 to 60 Hz
	Power Consumption	398W(Max), Standby<0.5W
Audible Noise	36/32 dBA (Normal/Economic mode)	
On-Screen Display Languages	Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages)	
Picture Modes	Dynamic/Presentation/sRGB/Cinema/(3D)/User 1/User 2	
Accessories	Standard	Optional
	Lens Cover	Spare Lamp Kit
	Remote Control w/ Battery	Ceiling Mount
	Power Cord (by region)	RS232 Cable
	User Manual CD	
	Quick Start Guide	
	Warranty Card (by region)	
	Carry bag	
	VGA(D-sub 15pin) Cable	


*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

MX722 Projector

Distance Chart

The screen aspect ratio is 4:3 and the projected picture is 4:3:


Screen size				Distance from screen (mm)			Vertical offset (mm)
Diagonal	W	H	Min length (max. zoom)	Average	Max length (min. zoom)		
Inch	mm	(mm)	(mm)	(max. zoom)		(min. zoom)	
40	1016	813	610	1231	1415	1600	46
50	1270	1016	762	1538	1769	2000	57
60	1524	1219	914	1846	2123	2400	69
70	1778	1422	1067	2154	2477	2800	80
80	2032	1626	1219	2462	2831	3200	91
90	2286	1829	1372	2769	3185	3600	103
100	2540	2032	1524	3077	3538	4000	114
120	3048	2438	1829	3692	4246	4800	137
150	3810	3048	2286	4615	5308	6000	171
200	5080	4064	3048	6154	7077	8000	229
250	6350	5080	3810	7692	8846	10000	286
300	7620	6096	4572	9231	10615	12000	343



Wall mount/Ceiling mount Chart

Ceiling mount installation

Ceiling Mount screw: M4
(Max L = 25 mm; Min L = 20 mm)



Unit: mm

Dimension



Unit: mm

