BenQ Digital Camera P860

Nothing can beat the thrill by taking a great shot and share your master piece with your friends and families. That is why BenQ DC P860 is the gadget you must have.

8 megapixels / 6x optical zoom 30x high zoom

With ultimate high zoom (totally up to 30X) plus the high resolution, every tiny detail can be presented sharply and clearly. You may capture the faraway objects and print them out in large size.

P/Av/Tv/M mode

P860 is provided with Av (adjust aperture to decide the depth of field), Tv (adjust shutter to decide exposure), Manual (adjust both aperture & shutter), and Program (set aperture/shutter automatically according to the environment) modes to satisfy even the photo expertise.

Large 2.5" TFT screen


Viewing on the screen can be enjoyable with DC P860's 2.5" large screen for your convenience.

Shake Free and High ISO portrait mode

You will no longer be troubled by those blurred photo caused by unexpected hand shaking or by the dark environment. New BenQ DC P860 equips with High ISO portriait and Shake-Free function that helps you to grasp sharp and clear images anytime, everytime.

AE-LOCK

Exposure and aperture settings can be locked directly in any situation without Auto-Focus to ensure appropriate lighting of the photos.



© 2007 BenQ Corporation. All rights Reserved. Corporate names and trademarks are the property of their respective comp Specifications subject to change without notice



Specification 8.0 Mega Pixels CCD; Size: 1/1.8 inch Sensor Optical: 6X; Digital: 5X Zoom f = 7.8 (W) ~ 46.8 (T) mm, (35mm film Lens equivalent: 37 ~222 mm); F/2.8(W)~4.8(T) Focus Range Normal: 30cm ~ Infinity Macro: 7cm LCD 2.5" TFT LCD / 153.6K pixels 3264 x 2448 (8M) / 3264 x 2175 (3:2) / **Image Resolution** 3264 x 1835 (16:9) / 2560 x 1920 (5M) / 1600 x 1200 (2M) / 640 x 480 (VGA) 640 x 480 / 320 x 240 (30fps) Movie Mode Continuous recording with sound Shutter Speed $1/1500 \sim 8 \text{ sec}$ Auto / Daylight / Cloudy / Tungsten / White Balance Fluorescent (H) / Fluorescent (L) / MWB Exposure $-2 \sim +2 \text{ EV} (0.3 \text{EV} / \text{step})$ Auto / 50 / 100 / 200 / 400 / 800 ISO / 1000 (Shake-Free mode) Flash Auto / Red eye reduction / Forced on / Slow sync / Forced off Self-Timer 2 sec / 10 sec AA Battery x 2 (ALKANIE or NiMH) Power Type Built-in 18 MB (Usable); Storage SD card compatible Still Image: JPEG (EXIF 2.2 compatible) File Format DCF compatible; Support DPOF Video: M JPEG / Audio: WAV 99.8 x 65 x 27.5 mm (42.5 with Lens Ring) Dimension/Weight 182 g (without battery & SD card) Digital output: USB 2.0 Interface Audio / Video output (NTSC/PAL) PictBridge Color Black USB cable / Software CD ROM / User Accessory Manual / Hand Strap / Pouch / AV Cable / NiMH AA battery x 2 / Battery Charger Set



