

BenQ Digital Camera DC C750

Highest C/P ratio 7Mp DSC with new BenQ style ID design Smile Catch (with default Face-Tracking enabled)

Provides **Smile Catch**, The newest feature can automatically track and trigger the shutter when a smiling face was detected

P/Av/Tv/M mode

Provide **Av** (adjust aperture), **Tv** (adjust shutter), **Manual** (adjust both aperture & shutter), and **Program** (aperture & shutter are automatically set according to the environment) modes to satisfy even the photo expertise.

Shake-Free mode

Shake-Free function can help you avoid blurred photo effect caused by unexpected hand shaking.

Face-Tracking function

C750 can automatically detect and track human faces and then focus to ensure the people are perfectly presented in terms of color and clearness in the photos.

3:2 and 16:9 special output size

3:2 resolution mode supported for easy printing without trimming edges; 16:9 resolution mode supported for direct display on 16:9 TV.

Various shooting modes

14 shooting modes are provided including Program / **Smile Catch** / Sunset / Backlight / Landscape / High ISO Portrait / Snow / Fireworks / Night Scene / Kids / Food / Building / Shake-Free / Text.

Photo frames embedded

Creative **photo frames** embedded for photos decoration.

Movie optical zoom

The optical zoom in movie mode allows you to zoom in and out for a sharp and clear view during the video recording.



Specifications

Sensor	7M Pixels CCD, Size: 1/2.5 inch	
Zoom	Optical: 3X / Digital: 4X	
Lens	f = 6.2 (W) ~ 18.6 (T) mm ; F = 2.8(W) ~ 5.2(T)	
Focus Range	Normal: 80cm ~ Infinity Macro: 15cm (W) / 40cm (T) ~ 1M	
LCD	2.5" LTPS LCD 150k pixels	
Image Resolution	3072 x 2304 (7M), 2048 x 1536 (3M), 640 x 480 (VGA)	3072 x 2048 (3:2) 2560 x 1920 (5M) 1024 x 768 (1M)
Movie Mode	720 x 400 (16:9) / 640 x 480 320 x 240 / 160 x 120 (30fps); M_JPEG movie format; Continuous recording with sound	
Shutter Speed	1/2000 ~ 8 sec	
White Balance	Auto / Daylight / Cloudy / Tungsten Fluorescent (H) / Fluorescent (L) / MWB	
Exposure	-2 ~ +2 EV (0.3EV / step)	
ISO	Auto / 50 / 100 / 200 / 400 / 800 / 1600	
Flash	Auto / Red eye reduction / Forced on Slow sync / Forced off	
Self-Timer	2 sec./10 sec./10+2 sec	
Power Source	AA Battery x 2 (Alkaline, Li-Ion, Oxyride or NiMH)	
Storage Type	Built-in 16 MB, Usable 6MB SD / SDHC card compatible	
File Format	Still Image: JPEG (EXIF 2.2 compatible) DCF compatible; Support DPOF; Audio: WAV W: 93.2 mm (w / Grip = 93.4)	
Dimensions / Weight	H: 62.2 mm T: 25.1 mm (w / LCD Cover = 25.9) under 140 g (w/o battery & SD card)	
Interface	Digital output: USB 2.0 Audio / Video output (NTSC/PAL)	
Accessory	USB cable / Software & UM CD ROM / Quick Guide/ Hand Strap / Pouch / AV Cable / Alkaline AA battery x 2	