

# BenQ WI060

## Digital Projector



Display Technology	DLP® by Texas Instruments®	
Native Resolution	1080p (1920 x 1080)	
Resolution Supported	VGA (640 x 480) to 1080p (1920 x 1080)	
Brightness	2000 ANSI Lumens	
Contrast Ratio	5000:1 (Full on / Full off)	
Image Size	26" to 300"	
Throw Ratio	1.59 - 1.9 (56.8" @ 2m)	
Zoom Ratio	1.15:1	
Keystone correction	1D, vertical +/- 40 degrees	
Lens	F = 2.50 ~ 2.76, f = 23.5 ~ 28.2 mm	
Lamp Life*	190W, 4500 / 6000 hours (Normal / Economic mode)	
Lamp Warranty	12 months or 2,000 cumulative hours whichever comes first	
Operational Noise	31 / 28 dB (Normal / Economic mode)	
Displayable Colours	Full 1.07 billion color palette	
Aspect Ratio	16:9 Native, 5 aspect ratio selectable	
Horizontal Frequency	31 ~ 90 kHz	
Vertical Scan Rate	48 ~ 86 Hz	
Interface	Computer in (D-sub 15pin) x 1 Composite Video in (RCA) x 1 S-Video in (Mini DIN 4pin) x 1 Component Video in x 1 (RCA x 3) Audio in (Mini Jack) x 1 Audio L/R in (RCA) x 2	Audio out (Mini Jack) x 1 Speaker 10W x 1 HDMI V1.3 x 2 USB (Type Mini B) x 1 (Download & Page up/down) RS232 (DB-9pin) x 1
Compatibility	Video Compatibility	NTSC / PAL / SECAM
	HDTV Compatibility	480i / 480p / 576i / 576p / 720p / 1080i / 1080p
Dimensions (HxWxD)	330 x 119.5 x 247 mm	
Weight	Net weight: 3.6 kg.   Gross weight: 4.6 kg.	
Auto Switching Power Supply	100 to 240 VAC, 50/60 Hz	
Power consumption	270W, Standby < 1W	
On Screen Display Languages	Czech / Danish / Dutch / English / Finnish / French / German / Italian / Japanese / Korean / Norwegian / Polish / Portuguese / Russian / Simplified Chinese / Spanish / Swedish / Thai / Traditional Chinese (19 Languages)	
Application Modes	Bright / Living Room / Gaming / Cinema / User 1 / User 2	
Functions	BrilliantColor™ Closed Captioning 3D Color Management Digital Zoom (x2) Freeze HDTV compatible	High Altitude Mode Quick Auto Search Wall Color Correction Blank Auto Off Security Password
Accessories Included	Quick Start Guide Manual CD Remote Control w/battery	VGA Cable Power Cord Carry Bag
Accessories Optional	Presentation Plus RS232 Cable	Spare Lamp Kit Ceiling mount

\* Lamp life results will vary depending on environmental conditions and usage.

All specifications are subject to change without notice. Available models (specs inc.) may vary from different regions.

