

Featuring 16:9 screen aspect ratio, flicker-free, low blue light technology, and Eye-protect sensor, the BL2420Z is tailor made to meet the exceptional screen performance and superb user experience.



BenQ LED Monitor BL2420Z





Low Blue Light

Every Monitor produces a strain of blue spectrum light that is one of the critical causes of eye damage, eye strain, headaches and sleeping disorders. BenQ's unique Low Blue Light technology is designed to deal with the everyday problem of blue light exposure and allows a healthier time spent in front of your computer. Switch to one of the four preset Low Blue Light Modes from OSD hot key (Multimedia – 30% reduction, Web-surfing – 50% reduction, Office – 60% reduction, Reading – 70% reduction), and reward your eyes without having to lose the visual enjoyment.



Flicker-Free Backlight

The flicker-free technology replaces conventional LED backlight to effectively eliminate flickering at all brightness levels, reducing eye fatigue caused by flickering backlight.



Eye-Protect Sensor

The Eye-Protect Sensor automatically sets the optimal brightness of the monitor screen by detecting the surrounding ambient light. This helps eliminate eyestrain and optimize the viewing condition all day long.



Eco Sensor

The Eye-Protect Sensor automatically sets the optimal brightness of the monitor screen by detecting the surrounding ambient light. This helps eliminate eyestrain and optimize the viewing condition all day long.



Height Adjustment Stand (HAS)

The HAS allows you to find the best viewing angles for personal work or screen sharing with an extensive range of monitor adjustments – height, tilt, pivot, stroke and swivel.

Product Name	BL2420Z
Product Color	Black/non Glossy black
Panel	
Back Light Unit	LED
LCD Size (inch)	23.8
Aspect Ratio	16.9
Resolution (max.)	1920×1080
Display Area (mm)	527.04×296.46
Pixel Pitch (mm)	0.275
Brightness (typ.)	250 cd/m²
Contrast (typ.)	3000:1
DCR (Dynamic Contrast Ratio) (typ.)	20M:1
Panel Type	TO-ACO-A-VA
Viewing Angle (L/R;U/D) (CR>=10)	178/178
Response Time	12ms, 7ms(GtG)
Display Colors	16.7million
Color Bit	8bits
Color Gamut	72% NTSC
Monitor	
Input Hor. Frequency (KHz)	30~83
Input Ver. Frequency (Hz)	50~ 76
Video Bandwidth (MHz)	205
TIGGO Dandwidd (Fil IZ)	D-sub / DVI / DP1.2 /
Input/Output Connector	headphone jack / line in
D 6 1 (00 2/4 AC)	Built-in
Power Supply (90~264 AC)	
Power Consumption(Base on Energy star)	23
Power Consumption(On mode)	42
Power Consumption(Eco mode)	22
Power Consumption(Power saving mode)	<0.5W
Power Consumption (Off mode)	<0.3W
K Locker	Yes
Disconsisted (LAMA Discon)	H: 524.9 × 563.2 × 239.55
Dimensions(HxWxD mm)	L: 384.9 × 563.2 × 239.55
Dimensions with Wall Mount	338.7 × 563.2 × 71.5
(HxWxD mm) (w/o Base)	536.7 X 363.2 X 71.5
Net Weight (kg)	7 7 7 7
Gross Weight (kg)	9.2
Feature	
Senseye3	Senseye 3
AMA	Yes
Win7	Yes
Win8	The second secon
	Yes
Win8.I	Yes
Mac Compatible	Yes
HDCP	Yes
Color Temperature	Normal (6500°K) / Reddish (5700°K) / Bluish (9300°K) / User Mode
OSD Language	17 languages
Speaker	IWx2
VESA Wall Mounting	100×100mm
Pivot 90°	90°
Swivel (left/right)	45 / 45
Tilt (°)	-5~20
Hight Adjustment (mm)	I40mm
Auto Pivot	Yes
Display Pilot	Yes
Low Blue Light	Yes
Flicker-free	Yes
Display Screen Coating	Anti-Glaire
Included Accessories	Message pulsarier in -
Signal cable	VGA cable(1.5m), USB2.0(1.5m)
0	



Dealer's Stamp

Product Name

