

# BenQ Digital Camera C1050



## 10 megapixels/ 3X optical zoom

With ultimate high image resolution, every tiny detail can be presented sharply and clearly. You may capture the faraway objects and print them out in large size.

## P/Av/Tv/M mode

C1050 is provided with **Av** (adjust aperture to decide the depth of field), **Tv** (adjust shutter to decide exposure), **Manual** (adjust both aperture & shutter), and **Program** (set aperture/shutter automatically according to the environment) modes to satisfy even the photo expertise.

## Large 2.5" LTPS screen

Viewing on the screen can be enjoyable with C1050's 2.5" large LTPS screen for your convenience.

## BenQ advanced new User Interface

BenQ new UI system enhances your using experience by offering ultra-friendly and beautiful interface.

## Shake-Free mode

You will no longer be troubled by those blurred photo caused by unexpected hand shaking.

## High ISO portrait supported

High sensitivity (ISO) **up to 1600** is supported in the capture mode to ensure clear photos in the dark.

## 3:2 and 16:9 special output size

3:2 resolution mode supported for easy printing without trimming edges; 16:9 resolution mode supported for direct display on 16:9 TV.

## Various scene modes

Totally 13 scene modes including Program / Sunset / Backlight / Landscape / High ISO Portrait / Snow / Fireworks / Night Scene / Kids / Food / Building / Shake-Free / Text.

## Specifications

<b>Sensor</b>	10.0 Mega Pixels CCD; Size: 1/1.8 inch
<b>Zoom</b>	Optical: 3X; Digital: 4X
<b>Lens</b>	f = 7.4 (W) ~ 22.2 (T) mm, (35mm film equivalent : 35.1 ~105.3 mm); F/2.8(W) ~ 5.1(T)
<b>Focus Range</b>	Normal: 40cm ~ Infinity Macro: 10cm
<b>LCD</b>	2.5" LTPS LCD / 153K pixels
<b>Image Resolution</b>	3648 x 2736 (10M) / 3648 x 2432 (3:2) / 3584 x 2016 (16:9) / 3264 x 2448 (8M) / 2560 x 1920 (5M) / 2048 x 1536 (3M) / 640 x 480 (VGA)
<b>Movie Mode</b>	640 x 480 / 320 x 240 / 160 x 120 (30fps) Continuous recording with sound
<b>Shutter Speed</b>	1/2000 ~ 8 sec
<b>White Balance</b>	Auto / Daylight / Cloudy / Tungsten / Fluorescent (H) / Fluorescent (L) / MWB
<b>Exposure</b>	-2 ~ +2 EV (0.3EV / step)
<b>ISO</b>	Auto / 50 / 100 / 200 / 400 / 800 / 1000
<b>Flash</b>	Auto / Red eye reduction / Forced on / Slow sync / Forced off
<b>Self-Timer</b>	2 sec. / 10 sec. / 10+2 sec
<b>Power Source</b>	AA Battery x 2 (Alkaline or NiMH)
<b>Storage Type</b>	Built-in 9 MB (Usable) SD card compatible
<b>File Format</b>	DCF compatible; Support DPOF Video: M_JPEG / Audio: WAV
<b>Dimensions / Weight</b>	91.5 x 61.5 x 32 mm (26 at slimmest) 140 g (without battery & SD card)
<b>Interface</b>	Digital output: USB 2.0 Audio / Video output ( NTSC/PAL)
<b>Accessory</b>	USB cable / Software CD ROM / User's Manual / Hand Strap / Pouch / AV Cable / NiMH AA battery x 2

# BENQ Digital Camera C1050

## More Information about this Camera

### Continuous Shooting till memory full

You are allowed to capture as many photos and videos as possible based on your SD memory card capacity.

### Printer mode supported

Easy for you to print photos out directly via the compatible printer (the printer with PictBridge logo) without connecting to the computer first.

### Movie optical zoom

The optical zoom in movie mode allows you to zoom in and out for a sharp and clear view during the video recording

## Difference between C1050 and C1000

Model	C1050	C1000
<b>Outlook</b>	Completely different ID	
<b>Specifications</b>		
<b>Image Resolution</b>	3648 x 2736 (10M) / 3648 x 2432 (3:2) / 3584 x 2016 (16:9) / 3264 x 2448(8M) / 2560 x 1920 (5M) / 2048 x 1536 (3M) / 640 x 480(VGA)	3648 x 2736 / 3648 x 2432 (3:2) / 3264 x 2448 / 2560 x 1920 / 2048 x 1536 / 640 x 480
<b>Lens</b>	f = 7.4 (W) ~ 22.2 (T) mm, (35mm film equivalent : 35.1 ~105.3 mm); F/2.8(W) ~ 5.1(T)	f = 7.94 ( W ) ~ 22.71 ( T ) mm, (35mm film equivalent : 38.01 ~108.73mm); F/2.8(W) ~ 5.1(T)
<b>LCD</b>	2.5" LTPS LCD / 153K pixels	2.4" TFT LCD / 112K pixels
<b>Dimensions</b>	91.5 x 61.5 x 32 mm	89 x 60.5 x 32.7 mm
<b>Storage</b>	Built-in 9MB	Built-in 24MB
<b>Focus Range</b>	Normal: 40cm ~ Infinity Macro: 10cm	Normal: 80cm ~ Infinity Macro: (W) 5cm ~ 80cm / (T) 25cm ~ 80cm
<b>White Balance</b>	Auto / Daylight / Cloudy / Tungsten / Fluorescent (H) / Fluorescent (L) / MWB	Auto / Daylight / Cloudy / Tungsten / Fluorescent (H) / Fluorescent (L) / Custom
<b>ISO</b>	Auto / 50 / 100 / 200 / 400 / 800 / 1000	Auto / 64 / 100 / 200