



BenQ DC X720



Product Features

World slimmest 7MP at just 12.5mm

7 mega pixels and 3X optical zoom

Large 2.5" LTPS 230K LCD

smc Pentax lens (Super Multi-Coating)

Dual Shake-Free system

Anti-shake in both movie and capture modes.

High ISO supported

ISO up to 4000 in movie mode; up to 1200 in capture mode.

Stainless steel casing with stylish outlook

4 colors for your options

Silver (stainless original color), Black, White, and Red.

Pictbridge supported

7 scene modes

Manual / Shake-Free / Portrait / Landscape / Night Scene / Sport / Back Light.

2G SD card supported

Specifications

Image Sensor	Panasonic 7.2 Mega Pixels CCD; Size: 1/2.5 inch
Image Resolution	3072 x 2304(7M) / 2560 x 1920 (5M) / 2048 x 1536 (3M) / 1600 x 1200(2M) / 640 x 480(VGA)
Lens	smc Pentax lens f = 6.2 (W) ~ 18.6 (T) mm, (35mm film equivalent : 37.5 ~112.5mm); F/2.7(W) ~ 4.3(T)
Zoom	Optical: 3X Digital: 4X(Preview) / 12X (Playback)
LCD	AUO 2.5" LTPS LCD / 230K Dot
Dimensions / Weight	91 x 60 x 14.7 (12.5 slimmest) mm / 120 g (without battery & SD card)
Power Source	720mAh Rechargeable Li-on Battery (CIPA 150)
Storage Type	Built-in 18 MB (Usable) 2G SD card compatible
Focus Range	Normal: 40cm ~ Infinity Macro: 15cm ~ 30 cm (Wide)
Shutter Speed	1/2000~1 sec (Scene mode 4 sec)
Movie Mode	Video: 640 x 480 / 320 x 240 / 160 x 128 (30fps) Continuous recording with sound
White Balance	Auto / Sunny / Cloudy / Tungsten / Fluorescent
Exposure	-2~+2 EV (0.3EV / step)
ISO	Auto / 80 / 160 / 320 / 400 / 800 / 1200 (Shake Free mode) / 4000 (Movie mode)
Flash	Auto/Red eye reduction/Forced on/Slow sync/Forced off
Self-Timer	2 sec./ 10 sec./ Intv.
File Format	Still Image: JPEG (EXIF 2.2 compatible), DCF compatible, Video: MPEG4 / Audio: WAV
Interface	Digital output: USB 2.0 (High Speed) Audio / Video output (NTSC/PAL) Pictbridge
Accessory	- USB cable - Software CD ROM - User's Manual - Hand Strap - Pouch - AV Cable - Li-on battery - Battery charger set