

TW526



| | |
|------------------------------------|---|
| Projection System | DLP |
| Native Resolution | WXGA (1280 x 800) |
| Brightness* | 3,200 ANSI Lumens |
| Contrast Ratio | 13,000:1 |
| Display Color | 1.07 Billion Colors |
| Lens | F= 2.56 - 2.8, f= 21 - 23.1 mm |
| Aspect Ratio | Native 16:10 (5 aspect ratio selectable) |
| Throw Ratio | 1.5 - 1.65 (62" @ 2m) |
| Image Size (Diagonal) | 53" - 300" |
| Zoom Ratio | 1.1:1 |
| Lamp Type | 190W |
| Keystone Adjustment | 1D, Vertical \pm 40 degrees |
| Projection Offset | 100% \pm 5% |
| Resolution Support | VGA (640 x 480) to UXGA (1600 x 1200) |
| Horizontal Frequency | 15 - 102 KHz |
| Vertical Scan Rate | 23 - 120 Hz |
| Interface | Computer in (D-sub 15pin) x 2 (Share with component) Monitor out (D-sub 15pin) x 1 Composite Video in (RCA) x 1 S-Video in (Mini DIN 4pin) x 1 HDMI x 1 Audio in (Mini Jack) x 1 Audio out (Mini Jack) x 1 Speaker 2W x 1 USB (Type B) x 1 RS232 (DB-9pin) x 1 IR Receiver x1 (Front) |
| Dimensions(W x H x D) | 283 x 95 x 222 mm |
| HDTV Compatibility | 480i, 480p, 576i, 576p, 720p, 1080i, 1080p |
| Video Compatibility | NTSC, PAL, SECAM |
| Weight | 1.9 kg |
| Audible Noise | 33 / 28 dBA (Normal / Economic mode) |
| Power Supply | AC100 to 240 V, 50 to 60 Hz |
| Power Consumption | Normal 270W, Eco 220W, Standby <0.5W |
| On-Screen Display Languages | Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages) |
| Picture Modes | Dynamic / Presentation / sRGB / Cinema / (3D) / User 1 / User 2 Remote Control w/ Battery Power Cord (by region) |
| Accessories (Standard) | UM Download Instruction and Regulatory Statements Quick Start Guide Warranty Card (by region) VGA(D-sub 15pin) Cable |

| | | |
|--|--|---|
| Accessories (Optional) | Spare Lamp Kit Ceiling Mount 3D Glasses Carry bag | |
| 3D Support and Compatibility | Frame Sequential: Up to 720p Frame Packing: Up to 1080p Side by Side: Up to 1080i/p Top Bottom: Up to 1080p | *Lamp life results will vary |
| Lamp Mode (Normal / Economic / SmartEco / LampSave) | 4500 / 6000 / 6500 / 10000 hours | depending on environmental conditions and usage. Actual |

product's features and specifications are subject to change without notice.