

BenQ MX750 Digital Projector



Projection System	DLP® by Texas Instruments®	
Native Resolution	XGA (1024 x 768)	
Resolution Supported	VGA (640 x 480) to UXGA (1600 x 1200)	
Brightness	3000 ANSI Lumens	
Contrast Ratio	3000:1 (Full on / Full off)	
Image Size	26" to 352"	
Throw Ratio	1.39 to 2.23 (70.6" @ 2M)	
Zoom Ratio	Manual Zoom, 1.6:1	
Keystone correction	Auto Keystone / Manual Vertical ± 40 Degree	
Lens	F = 2.68 (Wide) ~ 2.84 (Tele), f=15.9mm (Wide) ~ 25.5mm (Tele)	
Lamp Life	225W, 3000 / 4000 hours (Normal / Economic mode)	
Lamp Warranty	12 months or 2,000 cumulative hours whichever comes first	
Operational Noise	29 / 27 dB (Normal / Economic mode)	
Displayable Colours	Full 16.7 million color palette	
Aspect Ratio	4:3 Native, 16:9 Selectable	
Horizontal Frequency	31 ~ 93 kHz	
Vertical Scan Rate	48 ~ 120 Hz	
Input Terminals	PC: Analog RGB: D-sub 15 pin x 2 LAN networking: RJ-45 x1 (LAN Display) USB connector: - Type A x2 (USB thumb drive, mouse/ keypad control) - Type mini B x1 (USB display)	A/V: HDMI x1 S-Video: Mini Din 4 pin x 1 Composite Video: RCA x 1 Audio L/R : RCA x 2 Stereo Mini Jack x 1
Output Terminals	PC: D-sub 15 pin x 1 DC 12V T trigger x 1	Audio: Variable Audio Out: Stereo Mini Jack x 1 Speaker: 10W x 2
Control Terminals	Serial Connector: RS232 9 pin (male) RJ45 x1	USB connector: Type mini B x1
Video Compatibility	NTSC / PAL / SECAM	
HDTV Compatibility	480i / 480p / 576i / 576p / 720p / 1080i / 1080p	
Dimensions (HxWxD)	130 x 329.5 x 248.5 mm	
Weight	Net weight: 3.55 kg. Gross weight: 5.40 kg.	
Auto Switching Power Supply	100 to 240 VAC, 50 to 60 Hz	
Power consumption	250W, Standby < 1W	
On-Screen Display Language	Bulgarian / Croatian / Czech / Danish / Dutch / English / Finnish / French / German / Hungarian / Italian / Japanese / Korean / Norwegian / Polish / Portuguese / Romanian / Russian / Simplified Chinese / Spanish / Swedish / Turkish / Thai / Traditional Chinese (24 Languages)	
Picture Modes	Dynamic Mode sRGB Mode Presentation Mode	Cinema Mode User 1 Mode User 2 Mode
Functions	BrilliantColor™ Blank VID™ Panel Key Lock 3D Color Management Auto Off Crestron LAN Control Security Password Closed Captioning	HDTV Compatible Digital Zoom (x2) High Altitude Mode Variable Audio Out "Q?" Hot Key for FAQ Quick Cooling 3D Ready Quick Auto Search Freeze
Included accessories	Quick Start Guide Manual CD Remote Control w/battery	VGA Cable Power Cord Soft Carry Case
Accessories (Optional)	Presentation Plus Ceiling Mount	Spare Lamp Kit Wireless Dongle

All specifications are subject to change without notice.
Available models (specs inc.) may vary from different regions.



All our projectors are
RoHS compliant

