



MX717 Digital Projector

Highlights

- High Contrast Ratio
- LAN control
- BrilliantColor™
- 3D Ready



Projection System	DLP		
Native Resolution	XGA(1024 x 768)		
Brightness	4000 ANSI lumens		
Contrast Ratio	5300 : 1		
Display Color	1.07 Billion Colors		
Lens	F=2.59-2.87, f=16.88-21.88		
Aspect Ratio	Native 4:3 (5 aspect ratio selectable)		
Throw Ratio	1.51-1.97 (65"@ 2m)		
Image Size (Diagonal)	25"-300"		
Zoom Ratio	1.3:1		
Lamp Type	300W		
Lamp (Normal/Economic Mode)*	3000/4000 hours		
Keystone Adjustment	1D, Vertical +/- 40 degrees		
Projection Offset	115%±5%		
Resolution Support	VGA(640 x 480) to UXGA(1600 x 1200)		
Horizontal Frequency	31K-102KHz		
Vertical Scan Rate	23-120Hz		
Compatibility	HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	
	Video Compatibility	NTSC, PAL, SECAM	
		PC: 120Hz Frame Sequential 2D for resolutions up to	
		PC: 60Hz Frame Sequential 3D for resolutions up to WXGA,	
		PC: 60Hz Top-bottom 3D for resolutions up to SXGA+,	
		Video: 60Hz Frame Sequential 3D for resolutions up to 480i	
Interface	Computer in (D-sub 15pin)	x 2 (shared with D-sub 15pin)	
	Monitor out (D-sub 15pin)	x 1	
	HDMI (v1.3)	x 1	
	Composite Video in (RCA)	x 1	
	S-Video in (Mini DIN 4pin)	x 1	
	Audio in (Mini Jack)	x 1	
	Audio L/R in (RCA)	x 1	
	Audio out (Mini Jack)	x 1	
	Speaker	10W x 2	
	LAN (RJ45)	x 1	
	USB (Type Mini B)	x 1	
	RS232 (DB-9pin)	x 1	
	IR Receiver	x 2	
Dimensions	Dimensions(W x H x D)	339x120.5x238 mm	
	Weight	3.8 kg (8.27 lbs)	
Power	Power Supply	AC 100 to 240 V, 50/60 Hz	
	Power Consumption	398W, Standby<0.5W	
Audible Noise	35/30 dBA (Normal/Economic mode)		
On-Screen Display Languages	English/ France/ Germany/ Italian/ Spanish/ Russian/ Traditional Chinese/ Simplified Chinese/ Japanese/ Korean/ Swedish/ Dutch/ Turkish/ Czech/ Portuguese/ Thai/ Polish/ Hungarian/ Croatian/ Romanian/ Norwegian/ Danish/ Bulgaria/ Finnish/ Indonesian/ Greek/ Hindi/ Arabic (28 Languages)		
Picture Modes	Dynamic/Presentation/sRGB/Cinema/User 1/User 2		
Accessories	Standard	Optional	
	Remote Control w/ Battery	Presentation Plus	P/N: 65J9306.002
	Power Cord (by region)	Spare Lamp Kit	P/N: 5J.J5X05.001
	User Manual CD	3D Glasses	P/N: 5J.J0T14.011
	Quick Start Guide		
	Warranty Card (by region)		
	VGA(D-sub 15pin) Cable		

*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

MX717 Digital Projector

Distance Chart





Table A1: The screen aspect ratio is 4:3 and the projected picture is 4:3

Screen size		Size of the projected image		Distance from screen (mm)			Vertical offset (mm)
Diagonal		H (mm)	W (mm)	Min length	Average	Max length	
Inch	mm			(max. zoom)		(min. zoom)	
40	1016	610	813	1333	1467	1600	30
50	1270	762	1016	1667	1833	2000	38
60	1524	914	1219	2000	2200	2400	46
70	1778	1067	1422	2333	2567	2800	53
80	2032	1219	1626	2667	2933	3200	61
90	2286	1372	1829	3000	3300	3600	69
100	2540	1524	2032	3333	3667	4000	76
120	3048	1829	2438	4000	4400	4800	91
150	3810	2286	3048	5000	5500	6000	114
200	5080	3048	4064	6667	7333	8000	152
250	6350	3810	5080	8333	9167	10000	191
300	7620	4572	6096	10000	11000	12000	229

Ceiling mount Chart



單位：mm

Dimension

