

Make your vision come alive

Designed to meet the rising demands for large-sized viewing and ultra-high definition, the PD3200U & PD3200Q boasts a 32"W display built with BenQ's advanced IPS technology, providing creative professionals working space to work confidently in 100% sRGB and Rec.709 color spaces

Keyboard Video Mouse (KVM) Switch

KVM Switch function allows users to display and control the contents from two different PC systems on one screen using just one set of keyboard and mouse to save space and boost work efficiency.

2k QHD 2560x1440 resolution and IPS technology

PD3200Q is equipped with QHD resolution and IPS technology offering a wider viewing angle (178° in both horizontal and vertical planes) to users with exceptional clarity and vivid image quality in all angles.

4k UHD 3840x2160 resolution and IPS technology

PD3200U is equipped with QHD resolution and IPS technology offering a wider viewing angle (178° in both horizontal and vertical planes) to users with exceptional clarity and vivid image quality in all angles.

Darkroom/CAD/CAM/Animation modes for creative designers

The Darkroom mode adjusts the brightness and contrast of images giving clarity and sharpness to details, creating the optimal setting for work in darker post-processing environments. The revolutionary CAD/CAM Mode offers superior contrast on 3D color lines. You can clearly distinguish details in complicated object wireframes, alter monitor color and never miss a line again. The animation mode enhances details in dark shadows so you can fine-tune creations effortlessly, while areas that do not require this function remain unaltered.

Professionally Rendered Colors with 100% sRGB and Rec. 709

Work with 100% sRGB and Rec. 709 color space where more than 1 billion vibrant colors are accurately reproduced on the screen for professional photo editing and image viewing.

Key Features

- 100% Rec.709 and sRGB color space with IPS Technology
- DualView function
- Darkroom, CAD/CAM and Animation Display Mode
- Keyboard Video Mouse (KVM) Switch
- Eye-Care Technology

Secondary Features

- Hotkey Puck: external OSD controllers with 3 customizable preset keys
- Ergonomics: Customize your workstation for the perfect user environment with an extensive range of height, tilt, pivot, stroke and swivel monitor adjustments.



Product Name	PD3200Q	PD3200U
Display		
Screen Size	een Size 32"	
Panel Type	VA	IPS
Resolution (max.)	2560 × 1440	3840 × 2160 at 60Hz
Brightness (typ)	300	350
Native Contrast(typ.)	3000 : I	1000 : 1
Viewing Angle (L/R;U/D) (CR>=10)	178 / 178	
Response Time	4ms(G2G)
Aspect Ratio	16	:9
Display Colors	1.07	Billion
Color Gamut	100%	sRGB
Display Area(mm)	708.48 × 398.52	708.40 × 398.50
DCR (Dynamic Contrast Ratio)	20	M:I
Color Bit	10bits	
Audio		
Built-in Speaker	5W	′ × 2
Headphone Jack	Yes	
Audio Line In	Yes	
Special Features		
Color Temperature	Normal (6500°K) / Reddish (5700°K) / Bluish (9300°K) / User Mode	
Card Reader	Supported Formats : SD / SDHC / SDXCMMC	
HDCP	1.4 2.2	
VWSA Wall Mount	100 x 100 mm	
AMA	Yes	
Eye Care		
Flicker-free Technology	Yes	
Low Blue Light	Yes	
Eye Protector	Yes	
Display Screen Coating	Anti-Glare	
Professional		
Animation mode	Yes	Normal (6500K) / Reddish (5700K) / Bluish (9300K) / User Define
	Yes	
CAD/CAM mode	Y	es
CAD/CAM mode Dual View		es es
	Y	
Dual View	Y	ės
Dual View Video Format Support	Y Y Y	es es
Dual View Video Format Support KVM Switch	Y Y Y	es es
Dual View Video Format Support KVM Switch Auto Pivot	Y Y Y	es es es
Dual View Video Format Support KVM Switch Auto Pivot OSD controller/Hotkey Puck	Y Y Y	es es es
Dual View Video Format Support KVM Switch Auto Pivot OSD controller/Hotkey Puck Connectivity	Y Y Y Y Y HDMI 1.4 x I	es es es es
Dual View Video Format Support KVM Switch Auto Pivot OSD controller/Hotkey Puck Connectivity HDMI	Y Y Y Y Y HDMI I.4 × I	es es es HDMI 2.0 x 2
Dual View Video Format Support KVM Switch Auto Pivot OSD controller/Hotkey Puck Connectivity HDMI DisplayPort	Y Y Y Y Y Y Y Y Y Y Y D D D D D D D D D	es es es HDMI 2.0 × 2
Dual View Video Format Support KVM Switch Auto Pivot OSD controller/Hotkey Puck Connectivity HDMI DisplayPort USB	Y Y Y Y Y Y Y Y Y Y Y D D D D D D D D D	es ses ses HDMI 2.0 x 2 2 X I
Dual View Video Format Support KVM Switch Auto Pivot OSD controller/Hotkey Puck Connectivity HDMI DisplayPort USB Mini DisplayPort	Y Y Y Y Y Y Y Y Y Y Y D D D D D D D D D	es ses ses HDMI 2.0 x 2 2 X I
Dual View Video Format Support KVM Switch Auto Pivot OSD controller/Hotkey Puck Connectivity HDMI DisplayPort USB Mini DisplayPort Power	Y Y Y Y Y HDMI 1.4 x I DP I 3.0	es ses es HDMI 2.0 x 2 2 X I X 4 2 x I
Dual View Video Format Support KVM Switch Auto Pivot OSD controller/Hotkey Puck Connectivity HDMI DisplayPort USB Mini DisplayPort Power Max Power Consumption	Y Y Y Y Y HDMI 1.4 x I DP I 3.0 DP I	es ses ses HDMI 2.0 x 2 2 X I X 4 2 x I
Dual View Video Format Support KVM Switch Auto Pivot OSD controller/Hotkey Puck Connectivity HDMI DisplayPort USB Mini DisplayPort Power Max Power Consumption Power Consumption (Off mode)	Y Y Y Y Y HDMI 1.4 × 1 DP 1 3.0 DP 1 88W < 0.5W 35W	es ses ses ses ses ses ses ses ses ses
Dual View Video Format Support KVM Switch Auto Pivot OSD controller/Hotkey Puck Connectivity HDMI DisplayPort USB Mini DisplayPort Power Max Power Consumption Power Consumption (Off mode) Typical Power Consumption	Y Y Y Y Y HDMI 1.4 x I DP I 3.0 DP I 88W < 0.5W 35W	es ses ses ses ses ses ses ses ses ses
Dual View Video Format Support KVM Switch Auto Pivot OSD controller/Hotkey Puck Connectivity HDMI DisplayPort USB Mini DisplayPort Power Max Power Consumption Power Consumption (Off mode) Typical Power Consumption Voltage Rating	Y Y Y Y Y HDMI 1.4 x I DP I 3.0 DP I 88W < 0.5W 35W	es ses ses ses ses ses ses ses ses ses
Dual View Video Format Support KVM Switch Auto Pivot OSD controller/Hotkey Puck Connectivity HDMI DisplayPort USB Mini DisplayPort Power Max Power Consumption Power Consumption (Off mode) Typical Power Consumption Voltage Rating AC switch	Y Y Y Y Y Y HDMI 1.4 x 1 DP 1 3.0 DP 1 88W <0.5W 35W	es ses ses ses ses ses ses ses ses ses
Dual View Video Format Support KVM Switch Auto Pivot OSD controller/Hotkey Puck Connectivity HDMI DisplayPort USB Mini DisplayPort Power Max Power Consumption Power Consumption (Off mode) Typical Power Consumption Voltage Rating AC switch Dimension and Weight	HDMI 1.4 x I PP I 88W < 0.5W 35W H: 641.66 x 740.28 x 223.62	ess ess ess ess HDMI 2.0 x 2 2 X I X 4 .2 x I I10W <110W 44W
Dual View Video Format Support KVM Switch Auto Pivot OSD controller/Hotkey Puck Connectivity HDMI DisplayPort USB Mini DisplayPort Power Max Power Consumption Power Consumption (Off mode) Typical Power Consumption Voltage Rating AC switch Dimension and Weight Dimensions (H x W x D mm) Dimensions (H x W x D mm) (w/o Base)	HDMI 1.4 x I PP I 88W < 0.5W 35W 90 ~ 2 H: 641.66 x 740.28 x 223.62 436.42 x 74	ess ess ess ess HDMI 2.0 x 2 2 X I X 4 .2 x I I10W <110W 44W 44W 44W Lt: 491.66 x 740.28 x 223.62
Dual View Video Format Support KVM Switch Auto Pivot OSD controller/Hotkey Puck Connectivity HDMI DisplayPort USB Mini DisplayPort Power Max Power Consumption Power Consumption (Off mode) Typical Power Consumption Voltage Rating AC switch Dimension and Weight Dimensions (H x W x D mm) Dimensions (H x W x D mm) (w/o Base) Net Weight (kg) (without stand)	HDMI 1.4 × 1 PP 1 3.0 DP 1 88W < 0.5W 35W 90 ~ 2 0 H: 641.66 × 740.28 × 223.62 436.42 × 74	HDMI 2.0 x 2 2 X I X 4 2 X I I 10W <110W 44W 164 AC W L: 491.66 x 740.28 x 223.62 10.28 x 67.3
Dual View Video Format Support KVM Switch Auto Pivot OSD controller/Hotkey Puck Connectivity HDMI DisplayPort USB Mini DisplayPort Power Max Power Consumption Power Consumption (Off mode) Typical Power Consumption Voltage Rating AC switch Dimension and Weight Dimensions (H x W x D mm) Dimensions (H x W x D mm) (w/o Base) Net Weight (kg) (without stand) Tilt (down/up)	Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y	HDMI 2.0 x 2 2 X I X 4 2 X I I10W <110W 44W 164 AC W L: 491.66 x 740.28 x 223.62 10.28 x 67.3 5-20°
Dual View Video Format Support KVM Switch Auto Pivot OSD controller/Hotkey Puck Connectivity HDMI DisplayPort USB Mini DisplayPort Power Max Power Consumption Power Consumption (Off mode) Typical Power Consumption Voltage Rating AC switch Dimension and Weight Dimensions (H x W x D mm) Dimensions (H x W x D mm) (w/o Base) Net Weight (kg) (without stand) Tilt (down/up) Swivel (left/right)	HDMI 1.4 x I PP I 3.0 DP I 88W < 0.5W 35W 90 ~ 2 0 H: 641.66 x 740.28 x 223.62 436.42 x 74 8 .5° -4	ess ess ess ess HDMI 2.0 × 2 2 × I × 4 .2 × I I10W <110W 44W 164 AC W L: 491.66 × 740.28 × 223.62 10.28 × 67.3
Dual View Video Format Support KVM Switch Auto Pivot OSD controller/Hotkey Puck Connectivity HDMI DisplayPort USB Mini DisplayPort Power Max Power Consumption Power Consumption (Off mode) Typical Power Consumption Voltage Rating AC switch Dimension and Weight Dimensions (H x W x D mm) Dimensions (H x W x D mm) (w/o Base) Net Weight (kg) (without stand) Tilt (down/up)	HDMI 1.4 x 1 PP 1 3.0 DP 1 88W < 0.5W 35W 90 ~ 2 0 H: 641.66 x 740.28 x 223.62 436.42 x 74 8 -5° - 45°	ess ess ess ess ess HDMI 2.0 x 2 2 X I X 4 .2 x I I10W <110W 44W .64 AC W L: 491.66 x 740.28 x 223.62 40.28 x 67.3 .5 - 20° / 45°







